



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'sg.1'

\$ man sg.1

SG(1) User Commands SG(1)

NAME

sg - execute command as different group ID

SYNOPSIS

sg [-] [group [-c] command]

DESCRIPTION

The sg command works similar to newgrp but accepts a command. The command will be executed with the /bin/sh shell. With most shells you may run sg from, you need to enclose multi-word commands in quotes. Another difference between newgrp and sg is that some shells treat newgrp specially, replacing themselves with a new instance of a shell that newgrp creates. This doesn't happen with sg, so upon exit from a sg command you are returned to your previous group ID.

CONFIGURATION

The following configuration variables in /etc/login.defs change the behavior of this tool:

SYSLOG_SG_ENAB (boolean)

Enable "syslog" logging of sg activity.

FILES

`/etc/passwd`

User account information.

`/etc/shadow`

Secure user account information.

`/etc/group`

Group account information.

`/etc/gshadow`

Secure group account information.

SEE ALSO

`id(1)`, `login(1)`, `newgrp(1)`, `su(1)`, `gpasswd(1)`, `group(5)`, `gshadow(5)`.

shadow-utils 4.9

09/28/2022

SG(1)