Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'sg_rtpg.8'

$ man sg_rtpg.8

SG_RTPG(8)   SG3_UTILS   SG_RTPG(8)

NAME

    sg_rtpg - send SCSI REPORT TARGET PORT GROUPS command

SYNOPSIS

    sg_rtpg [--decode] [--help] [--hex] [--raw] [--readonly] [--verbose]

    [--version] DEVICE

DESCRIPTION

    Send a SCSI REPORT TARGET PORT GROUPS command to DEVICE and outputs the

    response.

    Target port group access is described in SPC-3 and SPC-4 found at

    www.t10.org . The most recent draft of SPC-4 is revision 37 in which

    target port groups are described in section 5.15 .

OPTIONS

    Arguments to long options are mandatory for short options as well.

    -d, --decode

        decodes the status code and asymmetric access state from each

        target port group descriptor returned. The default action is not

        to decode these values.

-e, --extended

    use extended header format for parameter data. This sets the PA?

    RAMETER DATA FORMAT field in the cdb to 1.

-h, --help

    output the usage message then exit.

-H, --hex

    output response in hex (rather than partially or fully decode

    it).

-r, --raw

    output response in binary to stdout.

-R, --readonly

    open the DEVICE read-only (e.g. in Unix with the O_RDONLY flag).

    The default is to open it read-write.

-v, --verbose

    increase the level of verbosity, (i.e. debug output).

-V, --version

    print the version string and then exit.

NOTES

The Report Target Port Groups command should be supported whenever the

TPGS bits in a standard INQUIRY response are greater than zero. [View

with sg_inq utility.]

EXIT STATUS

The exit status of sg_rtpg is 0 when it is successful. Otherwise see

the sg3_utils(8) man page.

AUTHORS

Written by Douglas Gilbert.

REPORTING BUGS

Report bugs to <dgilbert at interlog dot com>.

COPYRIGHT

Copyright ? 2004-2014 Christophe Varoqui and Douglas Gilbert

This software is distributed under a FreeBSD license. There is NO war?

ranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PUR?

POSE.

SEE ALSO

sg_inq(sg3_utils)