

Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'sg_scan.8'

\$ man sg_scan.8

SG_SCAN(8)

SG3_UTILS

SG_SCAN(8)

NAME

sg_scan - scans sg devices (or SCSI/ATAPI/ATA devices) and prints re?

sults

SYNOPSIS

sg_scan [-a] [-i] [-n] [-w] [-x] [DEVICE]*

DESCRIPTION

If no DEVICE names are given, sg_scan does a scan of the sg devices and outputs a line of information for each sg device that is currently bound to a SCSI device. If one or more DEVICEs are given only those de? vices are scanned. Each device is opened with the O_NONBLOCK flag so that the scan will not "hang" on any device that another process holds an O_EXCL lock on.

```
Any given DEVICE name is expected to comply with (to some extent) the
Storage Architecture Model (SAM see www.t10.org). Any device names as?
sociated with the Linux SCSI subsystem (e.g. /dev/sda and /dev/st0m)
are suitable. Devices names associated with ATAPI devices (e.g. most
CD/DVD drives and ATAPI tape drives) are also suitable. If the device
```

does not fall into the above categories then an ATA IDENTIFY command is tried.

In Linux 2.6 and 3 series kernels, the Isscsi utility may be helpful. Apart from providing more information (by data-mining in the sysfs pseudo file system), it does not need root permissions to execute, as this utility would typically need.

OPTIONS

- a do alphabetical scan (i.e. sga, sgb, sgc). Note that sg device nodes with an alphabetical index have been deprecated since the Linux kernel 2.2 series.
- -i do a SCSI INQUIRY, output results in a second (indented) line.
 If the device is an ATA disk then output information from an ATA
 IDENTIFY command
- -n do numeric scan (i.e. sg0, sg1...) [default]
- w use a read/write flag when opening sg device (default is read-only)
- -x extra information output about queueing

NOTES

This utility was written at a time when hotplugging of SCSI devices was not supported in Linux. It used a simple algorithm to scan sg device nodes in ascending numeric or alphabetical order, stopping after there were 4 consecutive errors.

In the Linux kernel 2.6 series, this utility uses sysfs to find which sg device nodes are active and only checks those. Hence there can be large "holes" in the numbering of sg device nodes (e.g. after an adapter has been removed) and still all active sg device nodes will be listed. This utility assumes that sg device nodes are named using the normal conventions and searches from /dev/sg0 to /dev/sg4095 inclusive.

EXIT STATUS

The exit status of sg_scan is 0 when it is successful. Otherwise see the sg3_utils(8) man page.

AUTHORS

Written by D. Gilbert and F. Jansen

COPYRIGHT

Copyright ? 1999-2013 Douglas Gilbert

This software is distributed under the GPL version 2. There is NO war?

ranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PUR?

POSE.

SEE ALSO

lsscsi(8)

sg3_utils-1.36

May 2013

SG_SCAN(8)