



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'shutdown.2'

\$ man shutdown.2

SHUTDOWN(2) Linux Programmer's Manual SHUTDOWN(2)

NAME

shutdown - shut down part of a full-duplex connection

SYNOPSIS

```
#include <sys/socket.h>
```

```
int shutdown(int sockfd, int how);
```

DESCRIPTION

The `shutdown()` call causes all or part of a full-duplex connection on the socket associated with `sockfd` to be shut down. If `how` is `SHUT_RD`, further receptions will be disallowed. If `how` is `SHUT_WR`, further transmissions will be disallowed. If `how` is `SHUT_RDWR`, further receptions and transmissions will be disallowed.

RETURN VALUE

On success, zero is returned. On error, -1 is returned, and `errno` is set appropriately.

ERRORS

`EBADF` `sockfd` is not a valid file descriptor.

`EINVAL` An invalid value was specified in `how` (but see `BUGS`).

ENOTCONN

The specified socket is not connected.

ENOTSOCK

The file descriptor sockfd does not refer to a socket.

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, 4.4BSD (shutdown() first appeared in 4.2BSD).

NOTES

The constants SHUT_RD, SHUT_WR, SHUT_RDWR have the value 0, 1, 2, respectively, and are defined in <sys/socket.h> since glibc-2.1.91.

BUGS

Checks for the validity of how are done in domain-specific code, and before Linux 3.7 not all domains performed these checks. Most notably, UNIX domain sockets simply ignored invalid values. This problem was fixed for UNIX domain sockets in Linux 3.7.

SEE ALSO

close(2), connect(2), socket(2), socket(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.