



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'snap-discard-ns.8'

\$ man snap-discard-ns.8

SNAP-DISCARD-NS(5) snappy SNAP-DISCARD-NS(5)

NAME

snap-discard-ns - internal tool for discarding preserved namespaces of snappy applications

SYNOPSIS

snap-discard-ns [--from-snap-confine] SNAP_INSTANCE_NAME

DESCRIPTION

The snap-discard-ns is a program used internally by snapd to discard a preserved mount namespace of a particular snap.

OPTIONS

The --from-snap-confine option is used internally by snap-confine to tell snap-discard-ns that it is invoked from snap-confine and can disable locking.

ENVIRONMENT

snap-discard-ns responds to the following environment variables

SNAP_CONFINE_DEBUG:

When defined the program will print additional diagnostic information about the actions being performed. All the output goes to stderr.

FILES

snap-discard-ns uses the following files:

/run/snapd/ns/\$SNAP_INSTANCE_NAME.mnt: /run/snapd/ns/\$SNAP_INSTANCE_NAME.*.mnt:

The preserved mount namespace that is unmounted and removed by snap-discard-ns. The second form is for the per-user mount namespace.

/run/snapd/ns/snap.\$SNAP_INSTANCE_NAME.fstab:

/run/snapd/ns/snap.\$SNAP_INSTANCE_NAME.*.user-fstab:

The current mount profile of a preserved mount namespace that is removed by snap-discard-ns.

BUGS

Please report all bugs with <https://bugs.launchpad.net/snapd/+filebug>

AUTHOR

zygmunt.krynicki@canonical.com

COPYRIGHT

Canonical Ltd.