



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'sssd-simple.5'

\$ man sssd-simple.5

SSSD-SIMPLE(5) File Formats and Conventions SSSD-SIMPLE(5)

NAME

sssd-simple - the configuration file for SSSD's 'simple' access-control provider

DESCRIPTION

This manual page describes the configuration of the simple access-control provider for sssd(8). For a detailed syntax reference, refer to the ?FILE FORMAT? section of the sssd.conf(5) manual page.

The simple access provider grants or denies access based on an access or deny list of user or group names. The following rules apply:

- ? If all lists are empty, access is granted
- ? If any list is provided, the order of evaluation is allow,deny.

This means that any matching deny rule will supersede any matched allow rule.

- ? If either or both "allow" lists are provided, all users are denied unless they appear in the list.
- ? If only "deny" lists are provided, all users are granted access unless they appear in the list.

CONFIGURATION OPTIONS

Refer to the section `?DOMAIN SECTIONS?` of the `sssd.conf(5)` manual page for details on the configuration of an SSSD domain.

`simple_allow_users` (string)

Comma separated list of users who are allowed to log in.

`simple_deny_users` (string)

Comma separated list of users who are explicitly denied access.

`simple_allow_groups` (string)

Comma separated list of groups that are allowed to log in. This applies only to groups within this SSSD domain. Local groups are not evaluated.

`simple_deny_groups` (string)

Comma separated list of groups that are explicitly denied access.

This applies only to groups within this SSSD domain. Local groups are not evaluated.

Specifying no values for any of the lists is equivalent to skipping it entirely. Beware of this while generating parameters for the simple provider using automated scripts.

Please note that it is an configuration error if both,

`simple_allow_users` and `simple_deny_users`, are defined.

EXAMPLE

The following example assumes that SSSD is correctly configured and `example.com` is one of the domains in the `[sssd]` section. This examples shows only the simple access provider-specific options.

```
[domain/example.com]
```

```
access_provider = simple
```

```
simple_allow_users = user1, user2
```

NOTES

The complete group membership hierarchy is resolved before the access check, thus even nested groups can be included in the access lists.

Please be aware that the `?ldap_group_nesting_level?` option may impact the results and should be set to a sufficient value. (`sssd-ldap(5)`)

option.

SEE ALSO

sssd(8), sssd.conf(5), sssd-ldap(5), sssd-ldap-attributes(5), sssd-krb5(5), sssd-simple(5), sssd-ipa(5), sssd-ad(5), sssd-files(5), sssd-sudo(5), sssd-session-recording(5), sss_cache(8), sss_debuglevel(8), sss_obfuscate(8), sss_seed(8), sssd_krb5_locator_plugin(8), sss_ssh_authorizedkeys(8), sss_ssh_knownhostsproxy(8), sssd-ifp(5), pam_sss(8). sss_rpcidmapd(5) sssd-systemtap(5)

AUTHORS

The SSSD upstream - <https://github.com/SSSD/sss/>

SSSD 07/10/2023 SSSD-SIMPLE(5)