



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd-backlight@.service.8'

\$ man systemd-backlight@.service.8

SYSTEMD-BACKLIGHT@.SERVICEsystemd-backlight@.servSYSTEMD-BACKLIGHT@.SERVICE(8)

NAME

systemd-backlight@.service, systemd-backlight - Load and save the display backlight brightness at boot and shutdown

SYNOPSIS

```
systemd-backlight@.service
/usr/lib/systemd/systemd-backlight save [backlight|leds]:DEVICE
/usr/lib/systemd/systemd-backlight load [backlight|leds]:DEVICE
```

DESCRIPTION

systemd-backlight@.service is a service that restores the display backlight brightness at early boot and saves it at shutdown. On disk, the backlight brightness is stored in /var/lib/systemd/backlight/. During loading, if the udev property ID_BACKLIGHT_CLAMP is not set to false, the brightness is clamped to a value of at least 1 or 5% of maximum brightness, whichever is greater. This restriction will be removed when the kernel allows user space to reliably set a brightness value which does not turn off the display.

KERNEL COMMAND LINE

systemd-backlight understands the following kernel command line

parameter:

`systemd.restore_state=`

Takes a boolean argument. Defaults to "1". If "0", does not restore the backlight settings on boot. However, settings will still be stored on shutdown.

SEE ALSO

`systemd(1)`

`systemd 252`

`SYSTEMD-BACKLIGHT@.SERVICE(8)`