



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd.index.7'

\$ man systemd.index.7

SYSTEMD.INDEX(7) systemd.index SYSTEMD.INDEX(7)

NAME

systemd.index - List all manpages from the systemd project

3

30-systemd-environment-d-generator(8) ? Load variables specified by environment.d

B

binfmt.d(5) ? Configure additional binary formats for executables at boot

bootctl(1) ? Control EFI firmware boot settings and manage boot loader

bootup(7) ? System bootup process

busctl(1) ? Introspect the bus

C

coredump.conf(5) ? Core dump storage configuration files

coredump.conf.d(5) ? Core dump storage configuration files

coredumpctl(1) ? Retrieve and process saved core dumps and metadata

crypttab(5) ? Configuration for encrypted block devices

D

daemon(7) ? Writing and packaging system daemons

dnsssec-trust-anchors.d(5) ? DNSSEC trust anchor configuration files

E

environment.d(5) ? Definition of user service environment

extension-release(5) ? Operating system identification

F

file-hierarchy(7) ? File system hierarchy overview

H

halt(8) ? Halt, power-off or reboot the machine

hostname(5) ? Local hostname configuration file

hostnamectl(1) ? Control the system hostname

hwdb(7) ? Hardware Database

I

init(1) ? systemd system and service manager

initrd-release(5) ? Operating system identification

integritytab(5) ? Configuration for integrity block devices

J

journal-remote.conf(5) ? Configuration files for the service accepting
remote journal uploads

journal-remote.conf.d(5) ? Configuration files for the service
accepting remote journal uploads

journal-upload.conf(5) ? Configuration files for the journal upload
service

journal-upload.conf.d(5) ? Configuration files for the journal upload
service

journalctl(1) ? Query the systemd journal

journal.conf(5) ? Journal service configuration files

journal.conf.d(5) ? Journal service configuration files

journal@.conf(5) ? Journal service configuration files

K

kernel-command-line(7) ? Kernel command line parameters

kernel-install(8) ? Add and remove kernel and initrd images to and from

/boot

L

libnss_myhostname.so.2(8) ? Hostname resolution for the locally configured system hostname

libnss_mymachines.so.2(8) ? Hostname resolution for local container instances

libnss_resolve.so.2(8) ? Hostname resolution via systemd-resolved.service

libnss_systemd.so.2(8) ? UNIX user and group name resolution for user/group lookup via Varlink

libudev(3) ? API for enumerating and introspecting local devices

linuxaa64.efi.stub(7) ? A simple UEFI kernel boot stub

linuxia32.efi.stub(7) ? A simple UEFI kernel boot stub

linuxx64.efi.stub(7) ? A simple UEFI kernel boot stub

loader.conf(5) ? Configuration file for systemd-boot

locale.conf(5) ? Configuration file for locale settings

localectl(1) ? Control the system locale and keyboard layout settings

localtime(5) ? Local timezone configuration file

logind(1) ? Control the systemd login manager

logind.conf(5) ? Login manager configuration files

logind.conf.d(5) ? Login manager configuration files

M

machine-id(5) ? Local machine ID configuration file

machine-info(5) ? Local machine information file

machinectl(1) ? Control the systemd machine manager

modules-load.d(5) ? Configure kernel modules to load at boot

N

nss-myhostname(8) ? Hostname resolution for the locally configured system hostname

nss-mymachines(8) ? Hostname resolution for local container instances

nss-resolve(8) ? Hostname resolution via systemd-resolved.service

nss-systemd(8) ? UNIX user and group name resolution for user/group lookup via Varlink

O

oomctl(1) ? Analyze the state stored in systemd-oomd
oomd.conf(5) ? Global systemd-oomd configuration files
oomd.conf.d(5) ? Global systemd-oomd configuration files
org.freedesktop.hostname1(5) ? The D-Bus interface of systemd-hostnamed
org.freedesktop.import1(5) ? The D-Bus interface of systemd-importd
org.freedesktop.locale1(5) ? The D-Bus interface of systemd-localed
org.freedesktop.LogControl1(5) ? D-Bus interface to query and set logging configuration
org.freedesktop.login1(5) ? The D-Bus interface of systemd-logind
org.freedesktop.machine1(5) ? The D-Bus interface of systemd-machined
org.freedesktop.oom1(5) ? The D-Bus interface of systemd-oomd
org.freedesktop.resolve1(5) ? The D-Bus interface of systemd-resolved
org.freedesktop.systemd1(5) ? The D-Bus interface of systemd
org.freedesktop.timedate1(5) ? The D-Bus interface of systemd-timedated
os-release(5) ? Operating system identification

P

pam_systemd(8) ? Register user sessions in the systemd login manager
poweroff(8) ? Halt, power-off or reboot the machine
pstore.conf(5) ? PStore configuration file
pstore.conf.d(5) ? PStore configuration file

R

rc-local.service(8) ? Compatibility generator and service to start /etc/rc.d/rc.local during boot
reboot(8) ? Halt, power-off or reboot the machine
repart.d(5) ? Partition Definition Files for Automatic Boot-Time Repartitioning
resolvconf(1) ? Resolve domain names, IPV4 and IPv6 addresses, DNS resource records, and services; introspect and reconfigure the DNS resolver
resolvectl(1) ? Resolve domain names, IPV4 and IPv6 addresses, DNS resource records, and services; introspect and reconfigure the DNS resolver
resolved.conf(5) ? Network Name Resolution configuration files

resolved.conf.d(5) ? Network Name Resolution configuration files

runlevel(8) ? Print previous and current SysV runlevel

S

sd-boot(7) ? A simple UEFI boot manager

sd-bus(3) ? A lightweight D-Bus IPC client library

sd-bus-errors(3) ? Standard D-Bus error names

sd-daemon(3) ? APIs for new-style daemons

sd-device(3) ? API for enumerating and introspecting local devices

sd-event(3) ? A generic event loop implementation

sd-hwdb(3) ? Read-only access to the hardware description database

sd-id128(3) ? APIs for processing 128-bit IDs

sd-journal(3) ? APIs for submitting and querying log entries to and from the journal

sd-login(3) ? APIs for tracking logins

sd-stub(7) ? A simple UEFI kernel boot stub

SD_ALERT(3) ? APIs for new-style daemons

sd_booted(3) ? Test whether the system is running the systemd init system

sd_bus_add_fallback(3) ? Declare properties and methods for a D-Bus path

sd_bus_add_fallback_vtable(3) ? Declare properties and methods for a D-Bus path

sd_bus_add_filter(3) ? Declare properties and methods for a D-Bus path

sd_bus_add_match(3) ? Add a match rule for incoming message dispatching

sd_bus_add_match_async(3) ? Add a match rule for incoming message dispatching

sd_bus_add_node_enumerator(3) ? Add a node enumerator for a D-Bus object path prefix

sd_bus_add_object(3) ? Declare properties and methods for a D-Bus path

sd_bus_add_object_manager(3) ? Add a D-Bus object manager for a D-Bus object sub-tree

sd_bus_add_object_vtable(3) ? Declare properties and methods for a D-Bus path

`sd_bus_attach_event(3)` ? Attach a bus connection object to an event loop

`sd_bus_call(3)` ? Invoke a D-Bus method call

`sd_bus_call_async(3)` ? Invoke a D-Bus method call

`sd_bus_call_method(3)` ? Initialize a bus message object and invoke the corresponding D-Bus method call

`sd_bus_call_method_async(3)` ? Initialize a bus message object and invoke the corresponding D-Bus method call

`sd_bus_call_method_asyncv(3)` ? Initialize a bus message object and invoke the corresponding D-Bus method call

`sd_bus_call_methodv(3)` ? Initialize a bus message object and invoke the corresponding D-Bus method call

`sd_bus_can_send(3)` ? Check which types can be sent over a bus object

`sd_bus_close(3)` ? Close and flush a bus connection

`sd_bus_close_unref(3)` ? Create a new bus object and create or destroy references to it

`sd_bus_close_unrefp(3)` ? Create a new bus object and create or destroy references to it

`sd_bus_creds_get_audit_login_uid(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_get_audit_session_id(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_get_augmented_mask(3)` ? Retrieve credentials object for the specified PID

`sd_bus_creds_get_cgroup(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_get_cmdline(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_get_comm(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_get_description(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_get_egid(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_get_euid(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_get_exe(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_get_fsgid(3)` ? Retrieve fields from a credentials object

sd_bus_creds_get_fsuid(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_gid(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_mask(3) ? Retrieve credentials object for the specified PID

sd_bus_creds_get_owner_uid(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_pid(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_ppid(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_selinux_context(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_session(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_sgid(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_slice(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_suid(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_supplementary_gids(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_tid(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_tid_comm(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_tty(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_uid(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_unique_name(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_unit(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_user_slice(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_user_unit(3) ? Retrieve fields from a credentials object

sd_bus_creds_get_well_known_names(3) ? Retrieve fields from a credentials object

sd_bus_creds_has_bounding_cap(3) ? Retrieve fields from a credentials object

sd_bus_creds_has_effective_cap(3) ? Retrieve fields from a credentials

object

`sd_bus_creds_has_inheritable_cap(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_has_permitted_cap(3)` ? Retrieve fields from a credentials object

`sd_bus_creds_new_from_pid(3)` ? Retrieve credentials object for the specified PID

`sd_bus_creds_ref(3)` ? Retrieve credentials object for the specified PID

`sd_bus_creds_unref(3)` ? Retrieve credentials object for the specified PID

`sd_bus_creds_unrefp(3)` ? Retrieve credentials object for the specified PID

`sd_bus_default(3)` ? Acquire a connection to a system or user bus

`sd_bus_default_flush_close(3)` ? Close and flush a bus connection

`sd_bus_default_system(3)` ? Acquire a connection to a system or user bus

`sd_bus_default_user(3)` ? Acquire a connection to a system or user bus

`sd_bus_destroy_t(3)` ? Define the callback function for resource cleanup

`sd_bus_detach_event(3)` ? Attach a bus connection object to an event loop

`sd_bus_emit_interfaces_added(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_emit_interfaces_added_strv(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_emit_interfaces_removed(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_emit_interfaces_removed_strv(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_emit_object_added(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_emit_object_removed(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_emit_properties_changed(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_emit_properties_changed_strv(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_emit_signal(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_emit_signalv(3)` ? Convenience functions for emitting (standard) D-Bus signals

`sd_bus_enqueue_for_read(3)` ? Re-enqueue a bus message on a bus connection, for reading

`sd_bus_error(3)` ? sd-bus error handling

`SD_BUS_ERROR_ACCESS_DENIED(3)` ? Standard D-Bus error names

`sd_bus_error_add_map(3)` ? Additional sd-dbus error mappings

`SD_BUS_ERROR_ADDRESS_IN_USE(3)` ? Standard D-Bus error names

`SD_BUS_ERROR_AUTH_FAILED(3)` ? Standard D-Bus error names

`SD_BUS_ERROR_BAD_ADDRESS(3)` ? Standard D-Bus error names

`sd_bus_error_copy(3)` ? sd-bus error handling

`SD_BUS_ERROR_DISCONNECTED(3)` ? Standard D-Bus error names

`SD_BUS_ERROR_END(3)` ? Additional sd-dbus error mappings

`SD_BUS_ERROR_FAILED(3)` ? Standard D-Bus error names

`SD_BUS_ERROR_FILE_EXISTS(3)` ? Standard D-Bus error names

`SD_BUS_ERROR_FILE_NOT_FOUND(3)` ? Standard D-Bus error names

`sd_bus_error_free(3)` ? sd-bus error handling

`sd_bus_error_get_errno(3)` ? sd-bus error handling

`sd_bus_error_has_name(3)` ? sd-bus error handling

`sd_bus_error_has_names(3)` ? sd-bus error handling

`sd_bus_error_has_names_sentinel(3)` ? sd-bus error handling

`SD_BUS_ERROR_INCONSISTENT_MESSAGE(3)` ? Standard D-Bus error names

`SD_BUS_ERROR_INTERACTIVE_AUTHORIZATION_REQUIRED(3)` ? Standard D-Bus error names

`SD_BUS_ERROR_INVALID_ARGS(3)` ? Standard D-Bus error names

`SD_BUS_ERROR_INVALID_SIGNATURE(3)` ? Standard D-Bus error names

`SD_BUS_ERROR_IO_ERROR(3)` ? Standard D-Bus error names

`sd_bus_error_is_set(3)` ? sd-bus error handling

`SD_BUS_ERROR_LIMITS_EXCEEDED(3)` ? Standard D-Bus error names

SD_BUS_ERROR_MAKE_CONST(3) ? sd-bus error handling

sd_bus_error_map(3) ? Additional sd-dbus error mappings

SD_BUS_ERROR_MAP(3) ? Additional sd-dbus error mappings

SD_BUS_ERROR_MATCH_RULE_INVALID(3) ? Standard D-Bus error names

SD_BUS_ERROR_MATCH_RULE_NOT_FOUND(3) ? Standard D-Bus error names

sd_bus_error_move(3) ? sd-bus error handling

SD_BUS_ERROR_NAME_HAS_NO_OWNER(3) ? Standard D-Bus error names

SD_BUS_ERROR_NO_MEMORY(3) ? Standard D-Bus error names

SD_BUS_ERROR_NO_NETWORK(3) ? Standard D-Bus error names

SD_BUS_ERROR_NO_REPLY(3) ? Standard D-Bus error names

SD_BUS_ERROR_NO_SERVER(3) ? Standard D-Bus error names

SD_BUS_ERROR_NOT_SUPPORTED(3) ? Standard D-Bus error names

SD_BUS_ERROR_NULL(3) ? sd-bus error handling

SD_BUS_ERROR_PROPERTY_READ_ONLY(3) ? Standard D-Bus error names

SD_BUS_ERROR_SERVICE_UNKNOWN(3) ? Standard D-Bus error names

sd_bus_error_set(3) ? sd-bus error handling

sd_bus_error_set_const(3) ? sd-bus error handling

sd_bus_error_set_errno(3) ? sd-bus error handling

sd_bus_error_set_errnof(3) ? sd-bus error handling

sd_bus_error_set_errnofv(3) ? sd-bus error handling

sd_bus_error_setf(3) ? sd-bus error handling

sd_bus_error_setfv(3) ? sd-bus error handling

SD_BUS_ERROR_TIMEOUT(3) ? Standard D-Bus error names

SD_BUS_ERROR_UNIX_PROCESS_ID_UNKNOWN(3) ? Standard D-Bus error names

SD_BUS_ERROR_UNKNOWN_INTERFACE(3) ? Standard D-Bus error names

SD_BUS_ERROR_UNKNOWN_METHOD(3) ? Standard D-Bus error names

SD_BUS_ERROR_UNKNOWN_OBJECT(3) ? Standard D-Bus error names

SD_BUS_ERROR_UNKNOWN_PROPERTY(3) ? Standard D-Bus error names

sd_bus_flush(3) ? Close and flush a bus connection

sd_bus_flush_close_unref(3) ? Create a new bus object and create or
destroy references to it

sd_bus_flush_close_unrefp(3) ? Create a new bus object and create or
destroy references to it

`sd_bus_get_address(3)` ? Set or query the address of the bus connection

`sd_bus_get_allow_interactive_authorization(3)` ? Set or query properties of a bus object

`sd_bus_get_bus_id(3)` ? Configure connection mode for a bus object

`sd_bus_get_close_on_exit(3)` ? Control whether to close the bus connection during the event loop exit phase

`sd_bus_get_connected_signal(3)` ? Control emission of local connection establishment signal on bus connections

`sd_bus_get_creds_mask(3)` ? Control feature negotiation on bus connections

`sd_bus_get_current_handler(3)` ? Query information of the callback a bus object is currently running

`sd_bus_get_current_message(3)` ? Query information of the callback a bus object is currently running

`sd_bus_get_current_slot(3)` ? Query information of the callback a bus object is currently running

`sd_bus_get_current_userdata(3)` ? Query information of the callback a bus object is currently running

`sd_bus_get_description(3)` ? Set or query properties of a bus object

`sd_bus_get_event(3)` ? Attach a bus connection object to an event loop

`sd_bus_get_events(3)` ? Get the file descriptor, I/O events and timeout to wait for from a message bus object

`sd_bus_get_exit_on_disconnect(3)` ? Control the exit behavior when the bus object disconnects

`sd_bus_get_fd(3)` ? Get the file descriptor, I/O events and timeout to wait for from a message bus object

`sd_bus_get_method_call_timeout(3)` ? Set or query the default D-Bus method call timeout of a bus object

`sd_bus_get_n_queued_read(3)` ? Get the number of pending bus messages in the read and write queues of a bus connection object

`sd_bus_get_n_queued_write(3)` ? Get the number of pending bus messages in the read and write queues of a bus connection object

`sd_bus_get_name_creds(3)` ? Query bus client credentials

`sd_bus_get_name_machine_id(3)` ? Retrieve a bus client's machine identity

`sd_bus_get_owner_creds(3)` ? Query bus client credentials

`sd_bus_get_property(3)` ? Set or query D-Bus service properties

`sd_bus_get_property_string(3)` ? Set or query D-Bus service properties

`sd_bus_get_property_strv(3)` ? Set or query D-Bus service properties

`sd_bus_get_property_trivial(3)` ? Set or query D-Bus service properties

`sd_bus_get_scope(3)` ? Set or query properties of a bus object

`sd_bus_get_sender(3)` ? Configure default sender for outgoing messages

`sd_bus_get_tid(3)` ? Set or query properties of a bus object

`sd_bus_get_timeout(3)` ? Get the file descriptor, I/O events and timeout to wait for from a message bus object

`sd_bus_get_unique_name(3)` ? Set or query properties of a bus object

`sd_bus_get_watch_bind(3)` ? Control socket binding watching on bus connections

`sd_bus_interface_name_is_valid(3)` ? Check if a string is a valid bus name or object path

`sd_bus_is_anonymous(3)` ? Set or query properties of a bus object

`sd_bus_is_bus_client(3)` ? Configure connection mode for a bus object

`sd_bus_is_monitor(3)` ? Configure connection mode for a bus object

`sd_bus_is_open(3)` ? Check whether the bus connection is open or ready

`sd_bus_is_ready(3)` ? Check whether the bus connection is open or ready

`sd_bus_is_server(3)` ? Configure connection mode for a bus object

`sd_bus_is_trusted(3)` ? Set or query properties of a bus object

`sd_bus_list_names(3)` ? Retrieve information about registered names on a bus

`sd_bus_match_signal(3)` ? Add a match rule for incoming message dispatching

`sd_bus_match_signal_async(3)` ? Add a match rule for incoming message dispatching

`sd_bus_member_name_is_valid(3)` ? Check if a string is a valid bus name or object path

`sd_bus_message_append(3)` ? Attach fields to a D-Bus message based on a

type string

sd_bus_message_append_array(3) ? Append an array of fields to a D-Bus message

sd_bus_message_append_array_iovec(3) ? Append an array of fields to a D-Bus message

sd_bus_message_append_array_memfd(3) ? Append an array of fields to a D-Bus message

sd_bus_message_append_array_space(3) ? Append an array of fields to a D-Bus message

sd_bus_message_append_basic(3) ? Attach a single field to a message

sd_bus_message_append_string_iovec(3) ? Attach a string to a message

sd_bus_message_append_string_memfd(3) ? Attach a string to a message

sd_bus_message_append_string_space(3) ? Attach a string to a message

sd_bus_message_append_strv(3) ? Attach an array of strings to a message

sd_bus_message_appendv(3) ? Attach fields to a D-Bus message based on a type string

sd_bus_message_at_end(3) ? Check if a message has been fully read

sd_bus_message_close_container(3) ? Create and move between containers in D-Bus messages

sd_bus_message_copy(3) ? Copy the contents of one message to another

sd_bus_message_dump(3) ? Produce a string representation of a message for debugging purposes

sd_bus_message_enter_container(3) ? Create and move between containers in D-Bus messages

sd_bus_message_exit_container(3) ? Create and move between containers in D-Bus messages

sd_bus_message_get_allow_interactive_authorization(3) ? Set and query bus message metadata

sd_bus_message_get_auto_start(3) ? Set and query bus message metadata

sd_bus_message_get_bus(3) ? Create a new bus message object and create or destroy references to it

sd_bus_message_get_cookie(3) ? Returns the transaction cookie of a message

sd_bus_message_get_creds(3) ? Query bus message addressing/credentials metadata

sd_bus_message_get_destination(3) ? Set and query bus message addressing information

sd_bus_message_get_errno(3) ? Query bus message addressing/credentials metadata

sd_bus_message_get_error(3) ? Query bus message addressing/credentials metadata

sd_bus_message_get_expect_reply(3) ? Set and query bus message metadata

sd_bus_message_get_interface(3) ? Set and query bus message addressing information

sd_bus_message_get_member(3) ? Set and query bus message addressing information

sd_bus_message_get_monotonic_usec(3) ? Retrieve the sender timestamps and sequence number of a message

sd_bus_message_get_path(3) ? Set and query bus message addressing information

sd_bus_message_get_realtime_usec(3) ? Retrieve the sender timestamps and sequence number of a message

sd_bus_message_get_reply_cookie(3) ? Returns the transaction cookie of a message

sd_bus_message_get_sender(3) ? Set and query bus message addressing information

sd_bus_message_get_seqnum(3) ? Retrieve the sender timestamps and sequence number of a message

sd_bus_message_get_signature(3) ? Query bus message signature

sd_bus_message_get_type(3) ? Query bus message addressing/credentials metadata

sd_bus_message_has_signature(3) ? Query bus message signature

sd_bus_message_is_empty(3) ? Query bus message signature

sd_bus_message_is_method_call(3) ? Query bus message addressing/credentials metadata

sd_bus_message_is_method_error(3) ? Query bus message

addressing/credentials metadata

sd_bus_message_is_signal(3) ? Query bus message addressing/credentials metadata

SD_BUS_MESSAGE_METHOD_CALL(3) ? Create a new bus message object and create or destroy references to it

SD_BUS_MESSAGE_METHOD_ERROR(3) ? Create a new bus message object and create or destroy references to it

SD_BUS_MESSAGE_METHOD_RETURN(3) ? Create a new bus message object and create or destroy references to it

sd_bus_message_new(3) ? Create a new bus message object and create or destroy references to it

sd_bus_message_new_method_call(3) ? Create a method call message

sd_bus_message_new_method_errno(3) ? Create an error reply for a method call

sd_bus_message_new_method_errnof(3) ? Create an error reply for a method call

sd_bus_message_new_method_error(3) ? Create an error reply for a method call

sd_bus_message_new_method_errorf(3) ? Create an error reply for a method call

sd_bus_message_new_method_return(3) ? Create a method call message

sd_bus_message_new_signal(3) ? Create a signal message

sd_bus_message_open_container(3) ? Create and move between containers in D-Bus messages

sd_bus_message_peek_type(3) ? Read a sequence of values from a message

sd_bus_message_read(3) ? Read a sequence of values from a message

sd_bus_message_read_array(3) ? Access an array of elements in a message

sd_bus_message_read_basic(3) ? Read a basic type from a message

sd_bus_message_read_strv(3) ? Access an array of strings in a message

sd_bus_message_read_strv_extend(3) ? Access an array of strings in a message

sd_bus_message_readv(3) ? Read a sequence of values from a message

sd_bus_message_ref(3) ? Create a new bus message object and create or

destroy references to it

`sd_bus_message_rewind(3)` ? Return to beginning of message or current container

`sd_bus_message_seal(3)` ? Prepare a D-Bus message for transmission

`sd_bus_message_send(3)` ? Queue a D-Bus message for transfer

`sd_bus_message_sensitive(3)` ? Mark a message object as containing sensitive data

`sd_bus_message_set_allow_interactive_authorization(3)` ? Set and query bus message metadata

`sd_bus_message_set_auto_start(3)` ? Set and query bus message metadata

`sd_bus_message_set_destination(3)` ? Set and query bus message addressing information

`sd_bus_message_set_expect_reply(3)` ? Set and query bus message metadata

`sd_bus_message_set_sender(3)` ? Set and query bus message addressing information

`SD_BUS_MESSAGE_SIGNAL(3)` ? Create a new bus message object and create or destroy references to it

`sd_bus_message_skip(3)` ? Skip elements in a bus message

`sd_bus_message_unref(3)` ? Create a new bus message object and create or destroy references to it

`sd_bus_message_unrefp(3)` ? Create a new bus message object and create or destroy references to it

`sd_bus_message_verify_type(3)` ? Check if the message has specified type at the current location

`SD_BUS_METHOD(3)` ? Declare properties and methods for a D-Bus path

`SD_BUS_METHOD_WITH_NAMES(3)` ? Declare properties and methods for a D-Bus path

`SD_BUS_METHOD_WITH_NAMES_OFFSET(3)` ? Declare properties and methods for a D-Bus path

`SD_BUS_METHOD_WITH_OFFSET(3)` ? Declare properties and methods for a D-Bus path

`sd_bus_negotiate_creds(3)` ? Control feature negotiation on bus connections

`sd_bus_negotiate_fds(3)` ? Control feature negotiation on bus connections

`sd_bus_negotiate_timestamp(3)` ? Control feature negotiation on bus connections

`sd_bus_new(3)` ? Create a new bus object and create or destroy references to it

`sd_bus_object_path_is_valid(3)` ? Check if a string is a valid bus name or object path

`sd_bus_open(3)` ? Acquire a connection to a system or user bus

`sd_bus_open_system(3)` ? Acquire a connection to a system or user bus

`sd_bus_open_system_machine(3)` ? Acquire a connection to a system or user bus

`sd_bus_open_system_remote(3)` ? Acquire a connection to a system or user bus

`sd_bus_open_system_with_description(3)` ? Acquire a connection to a system or user bus

`sd_bus_open_user(3)` ? Acquire a connection to a system or user bus

`sd_bus_open_user_machine(3)` ? Acquire a connection to a system or user bus

`sd_bus_open_user_with_description(3)` ? Acquire a connection to a system or user bus

`sd_bus_open_with_description(3)` ? Acquire a connection to a system or user bus

`SD_BUS_PARAM(3)` ? Declare properties and methods for a D-Bus path

`sd_bus_path_decode(3)` ? Convert an external identifier into an object path and back

`sd_bus_path_decode_many(3)` ? Convert an external identifier into an object path and back

`sd_bus_path_encode(3)` ? Convert an external identifier into an object path and back

`sd_bus_path_encode_many(3)` ? Convert an external identifier into an object path and back

`sd_bus_process(3)` ? Drive the connection

`SD_BUS_PROPERTY(3)` ? Declare properties and methods for a D-Bus path

`sd_bus_query_sender_creds(3)` ? Query bus message sender credentials/privileges

`sd_bus_query_sender_privilege(3)` ? Query bus message sender credentials/privileges

`sd_bus_ref(3)` ? Create a new bus object and create or destroy references to it

`sd_bus_release_name(3)` ? Request or release a well-known service name on a bus

`sd_bus_release_name_async(3)` ? Request or release a well-known service name on a bus

`sd_bus_reply_method_errno(3)` ? Reply with an error to a D-Bus method call

`sd_bus_reply_method_errnof(3)` ? Reply with an error to a D-Bus method call

`sd_bus_reply_method_errnofv(3)` ? Reply with an error to a D-Bus method call

`sd_bus_reply_method_error(3)` ? Reply with an error to a D-Bus method call

`sd_bus_reply_method_errorf(3)` ? Reply with an error to a D-Bus method call

`sd_bus_reply_method_errorfv(3)` ? Reply with an error to a D-Bus method call

`sd_bus_reply_method_return(3)` ? Reply to a D-Bus method call

`sd_bus_reply_method_returnv(3)` ? Reply to a D-Bus method call

`sd_bus_request_name(3)` ? Request or release a well-known service name on a bus

`sd_bus_request_name_async(3)` ? Request or release a well-known service name on a bus

`sd_bus_send(3)` ? Queue a D-Bus message for transfer

`sd_bus_send_to(3)` ? Queue a D-Bus message for transfer

`sd_bus_service_name_is_valid(3)` ? Check if a string is a valid bus name or object path

`sd_bus_set_address(3)` ? Set or query the address of the bus connection

`sd_bus_set_allow_interactive_authorization(3)` ? Set or query properties of a bus object

`sd_bus_set_anonymous(3)` ? Set or query properties of a bus object

`sd_bus_set_bus_client(3)` ? Configure connection mode for a bus object

`sd_bus_set_close_on_exit(3)` ? Control whether to close the bus connection during the event loop exit phase

`sd_bus_set_connected_signal(3)` ? Control emission of local connection establishment signal on bus connections

`sd_bus_set_description(3)` ? Set or query properties of a bus object

`sd_bus_set_exec(3)` ? Set or query the address of the bus connection

`sd_bus_set_exit_on_disconnect(3)` ? Control the exit behavior when the bus object disconnects

`sd_bus_set_fd(3)` ? Set the file descriptors to use for bus communication

`sd_bus_set_method_call_timeout(3)` ? Set or query the default D-Bus method call timeout of a bus object

`sd_bus_set_monitor(3)` ? Configure connection mode for a bus object

`sd_bus_set_property(3)` ? Set or query D-Bus service properties

`sd_bus_set_propertyv(3)` ? Set or query D-Bus service properties

`sd_bus_set_sender(3)` ? Configure default sender for outgoing messages

`sd_bus_set_server(3)` ? Configure connection mode for a bus object

`sd_bus_set_trusted(3)` ? Set or query properties of a bus object

`sd_bus_set_watch_bind(3)` ? Control socket binding watching on bus connections

`SD_BUS_SIGNAL(3)` ? Declare properties and methods for a D-Bus path

`SD_BUS_SIGNAL_WITH_NAMES(3)` ? Declare properties and methods for a D-Bus path

`sd_bus_slot_get_bus(3)` ? Query information attached to a bus slot object

`sd_bus_slot_get_current_handler(3)` ? Query information attached to a bus slot object

`sd_bus_slot_get_current_message(3)` ? Query information attached to a

bus slot object

sd_bus_slot_get_current_userdata(3) ? Query information attached to a

bus slot object

sd_bus_slot_get_description(3) ? Set or query the description of bus

slot objects

sd_bus_slot_get_destroy_callback(3) ? Define the callback function for

resource cleanup

sd_bus_slot_get_floating(3) ? Control whether a bus slot object is

"floating"

sd_bus_slot_get_userdata(3) ? Set and query the value in the "userdata"

field

sd_bus_slot_ref(3) ? Create and destroy references to a bus slot object

sd_bus_slot_set_description(3) ? Set or query the description of bus

slot objects

sd_bus_slot_set_destroy_callback(3) ? Define the callback function for

resource cleanup

sd_bus_slot_set_floating(3) ? Control whether a bus slot object is

"floating"

sd_bus_slot_set_userdata(3) ? Set and query the value in the "userdata"

field

sd_bus_slot_unref(3) ? Create and destroy references to a bus slot

object

sd_bus_slot_unrefp(3) ? Create and destroy references to a bus slot

object

sd_bus_start(3) ? Initiate a bus connection to the D-bus broker daemon

sd_bus_track_add_name(3) ? Add, remove and retrieve bus peers tracked

in a bus peer tracking object

sd_bus_track_add_sender(3) ? Add, remove and retrieve bus peers tracked

in a bus peer tracking object

sd_bus_track_contains(3) ? Add, remove and retrieve bus peers tracked

in a bus peer tracking object

sd_bus_track_count(3) ? Add, remove and retrieve bus peers tracked in a

bus peer tracking object

`sd_bus_track_count_name(3)` ? Add, remove and retrieve bus peers tracked in a bus peer tracking object

`sd_bus_track_count_sender(3)` ? Add, remove and retrieve bus peers tracked in a bus peer tracking object

`sd_bus_track_first(3)` ? Add, remove and retrieve bus peers tracked in a bus peer tracking object

`sd_bus_track_get_bus(3)` ? Track bus peers

`sd_bus_track_get_destroy_callback(3)` ? Define the callback function for resource cleanup

`sd_bus_track_get_recursive(3)` ? Track bus peers

`sd_bus_track_get_userdata(3)` ? Track bus peers

`sd_bus_track_new(3)` ? Track bus peers

`sd_bus_track_next(3)` ? Add, remove and retrieve bus peers tracked in a bus peer tracking object

`sd_bus_track_ref(3)` ? Track bus peers

`sd_bus_track_remove_name(3)` ? Add, remove and retrieve bus peers tracked in a bus peer tracking object

`sd_bus_track_remove_sender(3)` ? Add, remove and retrieve bus peers tracked in a bus peer tracking object

`sd_bus_track_set_destroy_callback(3)` ? Define the callback function for resource cleanup

`sd_bus_track_set_recursive(3)` ? Track bus peers

`sd_bus_track_set_userdata(3)` ? Track bus peers

`sd_bus_track_unref(3)` ? Track bus peers

`sd_bus_track_unrefp(3)` ? Track bus peers

`sd_bus_unref(3)` ? Create a new bus object and create or destroy references to it

`sd_bus_unrefp(3)` ? Create a new bus object and create or destroy references to it

`SD_BUS_VTABLE_CAPABILITY(3)` ? Declare properties and methods for a D-Bus path

`SD_BUS_VTABLE_END(3)` ? Declare properties and methods for a D-Bus path

`SD_BUS_VTABLE_START(3)` ? Declare properties and methods for a D-Bus

path

sd_bus_wait(3) ? Wait for I/O on a bus connection

SD_BUS_WRITABLE_PROPERTY(3) ? Declare properties and methods for a
D-Bus path

SD_CRIT(3) ? APIs for new-style daemons

SD_DEBUG(3) ? APIs for new-style daemons

sd_device_get_devname(3) ? Returns various fields of device objects

sd_device_get_devnum(3) ? Returns various fields of device objects

sd_device_get_devpath(3) ? Returns various fields of device objects

sd_device_get_devtype(3) ? Returns various fields of device objects

sd_device_get_diskseq(3) ? Returns various fields of device objects

sd_device_get_driver(3) ? Returns various fields of device objects

sd_device_get_ifindex(3) ? Returns various fields of device objects

sd_device_get_subsystem(3) ? Returns various fields of device objects

sd_device_get_sysname(3) ? Returns various fields of device objects

sd_device_get_sysnum(3) ? Returns various fields of device objects

sd_device_get_syspath(3) ? Returns various fields of device objects

sd_device_ref(3) ? Create or destroy references to a device object

sd_device_unref(3) ? Create or destroy references to a device object

sd_device_unrefp(3) ? Create or destroy references to a device object

SD_EMERG(3) ? APIs for new-style daemons

SD_ERR(3) ? APIs for new-style daemons

sd_event(3) ? Acquire and release an event loop object

sd_event_add_child(3) ? Add a child process state change event source
to an event loop

sd_event_add_child_pidfd(3) ? Add a child process state change event
source to an event loop

sd_event_add_defer(3) ? Add static event sources to an event loop

sd_event_add_exit(3) ? Add static event sources to an event loop

sd_event_add_inotify(3) ? Add an "inotify" file system inode event
source to an event loop

sd_event_add_inotify_fd(3) ? Add an "inotify" file system inode event
source to an event loop

`sd_event_add_io(3)` ? Add an I/O event source to an event loop

`sd_event_add_post(3)` ? Add static event sources to an event loop

`sd_event_add_signal(3)` ? Add a UNIX process signal event source to an event loop

`sd_event_add_time(3)` ? Add a timer event source to an event loop

`sd_event_add_time_relative(3)` ? Add a timer event source to an event loop

`SD_EVENT_ARMED(3)` ? Low-level event loop operations

`sd_event_child_handler_t(3)` ? Add a child process state change event source to an event loop

`sd_event_default(3)` ? Acquire and release an event loop object

`sd_event_destroy_t(3)` ? Define the callback function for resource cleanup

`sd_event_dispatch(3)` ? Low-level event loop operations

`sd_event_exit(3)` ? Ask the event loop to exit

`SD_EVENT_EXITING(3)` ? Low-level event loop operations

`SD_EVENT_FINISHED(3)` ? Low-level event loop operations

`sd_event_get_exit_code(3)` ? Ask the event loop to exit

`sd_event_get_fd(3)` ? Obtain a file descriptor to poll for event loop events

`sd_event_get_iteration(3)` ? Low-level event loop operations

`sd_event_get_state(3)` ? Low-level event loop operations

`sd_event_get_tid(3)` ? Acquire and release an event loop object

`sd_event_get_watchdog(3)` ? Enable event loop watchdog support

`sd_event_handler_t(3)` ? Add static event sources to an event loop

`SD_EVENT_INITIAL(3)` ? Low-level event loop operations

`sd_event_inotify_handler_t(3)` ? Add an "inotify" file system inode event source to an event loop

`sd_event_io_handler_t(3)` ? Add an I/O event source to an event loop

`sd_event_loop(3)` ? Run an event loop

`sd_event_new(3)` ? Acquire and release an event loop object

`sd_event_now(3)` ? Retrieve current event loop iteration timestamp

`SD_EVENT_OFF(3)` ? Enable or disable event sources

SD_EVENT_ON(3) ? Enable or disable event sources

SD_EVENT_ONESHOT(3) ? Enable or disable event sources

SD_EVENT_PENDING(3) ? Low-level event loop operations

sd_event_prepare(3) ? Low-level event loop operations

SD_EVENT_PREPARING(3) ? Low-level event loop operations

SD_EVENT_PRIORITY_IDLE(3) ? Set or retrieve the priority of event sources

SD_EVENT_PRIORITY_IMPORTANT(3) ? Set or retrieve the priority of event sources

SD_EVENT_PRIORITY_NORMAL(3) ? Set or retrieve the priority of event sources

sd_event_ref(3) ? Acquire and release an event loop object

sd_event_run(3) ? Run an event loop

SD_EVENT_RUNNING(3) ? Low-level event loop operations

sd_event_set_signal_exit(3) ? Automatically leave event loop on SIGINT and SIGTERM

sd_event_set_watchdog(3) ? Enable event loop watchdog support

sd_event_signal_handler_t(3) ? Add a UNIX process signal event source to an event loop

SD_EVENT_SIGNAL_PROCMASK(3) ? Add a UNIX process signal event source to an event loop

sd_event_source(3) ? Add an I/O event source to an event loop

sd_event_source_disable_unref(3) ? Increase or decrease event source reference counters

sd_event_source_disable_unrefp(3) ? Increase or decrease event source reference counters

sd_event_source_get_child_pid(3) ? Add a child process state change event source to an event loop

sd_event_source_get_child_pidfd(3) ? Add a child process state change event source to an event loop

sd_event_source_get_child_pidfd_own(3) ? Add a child process state change event source to an event loop

sd_event_source_get_child_process_own(3) ? Add a child process state

change event source to an event loop

`sd_event_source_get_description(3)` ? Set or retrieve descriptive names of event sources

`sd_event_source_get_destroy_callback(3)` ? Define the callback function for resource cleanup

`sd_event_source_get_enabled(3)` ? Enable or disable event sources

`sd_event_source_get_event(3)` ? Retrieve the event loop of an event source

`sd_event_source_get_exit_on_failure(3)` ? Set or retrieve the exit-on-failure feature of event sources

`sd_event_source_get_floating(3)` ? Set or retrieve 'floating' state of event sources

`sd_event_source_get_inotify_mask(3)` ? Add an "inotify" file system inode event source to an event loop

`sd_event_source_get_io_events(3)` ? Add an I/O event source to an event loop

`sd_event_source_get_io_fd(3)` ? Add an I/O event source to an event loop

`sd_event_source_get_io_fd_own(3)` ? Add an I/O event source to an event loop

`sd_event_source_get_io_revents(3)` ? Add an I/O event source to an event loop

`sd_event_source_get_pending(3)` ? Determine pending state of event sources

`sd_event_source_get_priority(3)` ? Set or retrieve the priority of event sources

`sd_event_source_get_ratelimit(3)` ? Configure rate limiting on event sources

`sd_event_source_get_signal(3)` ? Add a UNIX process signal event source to an event loop

`sd_event_source_get_time(3)` ? Add a timer event source to an event loop

`sd_event_source_get_time_accuracy(3)` ? Add a timer event source to an event loop

`sd_event_source_get_time_clock(3)` ? Add a timer event source to an

event loop

`sd_event_source_get_userdata(3)` ? Set or retrieve user data pointer of event sources

`sd_event_source_is_ratelimited(3)` ? Configure rate limiting on event sources

`sd_event_source_ref(3)` ? Increase or decrease event source reference counters

`sd_event_source_send_child_signal(3)` ? Add a child process state change event source to an event loop

`sd_event_source_set_child_pidfd_own(3)` ? Add a child process state change event source to an event loop

`sd_event_source_set_child_process_own(3)` ? Add a child process state change event source to an event loop

`sd_event_source_set_description(3)` ? Set or retrieve descriptive names of event sources

`sd_event_source_set_destroy_callback(3)` ? Define the callback function for resource cleanup

`sd_event_source_set_enabled(3)` ? Enable or disable event sources

`sd_event_source_set_exit_on_failure(3)` ? Set or retrieve the exit-on-failure feature of event sources

`sd_event_source_set_floating(3)` ? Set or retrieve 'floating' state of event sources

`sd_event_source_set_io_events(3)` ? Add an I/O event source to an event loop

`sd_event_source_set_io_fd(3)` ? Add an I/O event source to an event loop

`sd_event_source_set_io_fd_own(3)` ? Add an I/O event source to an event loop

`sd_event_source_set_prepare(3)` ? Set a preparation callback for event sources

`sd_event_source_set_priority(3)` ? Set or retrieve the priority of event sources

`sd_event_source_set_ratelimit(3)` ? Configure rate limiting on event sources

`sd_event_source_set_ratelimit_expire_callback(3)` ? Configure rate limiting on event sources

`sd_event_source_set_time(3)` ? Add a timer event source to an event loop

`sd_event_source_set_time_accuracy(3)` ? Add a timer event source to an event loop

`sd_event_source_set_time_relative(3)` ? Add a timer event source to an event loop

`sd_event_source_set_userdata(3)` ? Set or retrieve user data pointer of event sources

`sd_event_source_unref(3)` ? Increase or decrease event source reference counters

`sd_event_source_unrefp(3)` ? Increase or decrease event source reference counters

`sd_event_time_handler_t(3)` ? Add a timer event source to an event loop

`sd_event_unref(3)` ? Acquire and release an event loop object

`sd_event_unrefp(3)` ? Acquire and release an event loop object

`sd_event_wait(3)` ? Low-level event loop operations

`sd_get_machine_names(3)` ? Determine available seats, sessions, logged in users and virtual machines/containers

`sd_get_seats(3)` ? Determine available seats, sessions, logged in users and virtual machines/containers

`sd_get_sessions(3)` ? Determine available seats, sessions, logged in users and virtual machines/containers

`sd_get_uids(3)` ? Determine available seats, sessions, logged in users and virtual machines/containers

`sd_hwdb_enumerate(3)` ? Seek to a location in hwdb or access entries

`SD_HWDB_FOREACH_PROPERTY(3)` ? Seek to a location in hwdb or access entries

`sd_hwdb_get(3)` ? Seek to a location in hwdb or access entries

`sd_hwdb_new(3)` ? Create a new hwdb object and create or destroy references to it

`sd_hwdb_new_from_path(3)` ? Create a new hwdb object and create or destroy references to it

sd_hwdb_ref(3) ? Create a new hwdb object and create or destroy references to it

sd_hwdb_seek(3) ? Seek to a location in hwdb or access entries

sd_hwdb_unref(3) ? Create a new hwdb object and create or destroy references to it

SD_ID128_ALLF(3) ? APIs for processing 128-bit IDs

SD_ID128_CONST_STR(3) ? APIs for processing 128-bit IDs

sd_id128_equal(3) ? APIs for processing 128-bit IDs

SD_ID128_FORMAT_STR(3) ? APIs for processing 128-bit IDs

SD_ID128_FORMAT_VAL(3) ? APIs for processing 128-bit IDs

sd_id128_from_string(3) ? Format or parse 128-bit IDs as strings

sd_id128_get_boot(3) ? Retrieve 128-bit IDs

sd_id128_get_boot_app_specific(3) ? Retrieve 128-bit IDs

sd_id128_get_invocation(3) ? Retrieve 128-bit IDs

sd_id128_get_machine(3) ? Retrieve 128-bit IDs

sd_id128_get_machine_app_specific(3) ? Retrieve 128-bit IDs

sd_id128_in_set(3) ? APIs for processing 128-bit IDs

sd_id128_in_set_sentinel(3) ? APIs for processing 128-bit IDs

sd_id128_in_setv(3) ? APIs for processing 128-bit IDs

sd_id128_is_allf(3) ? APIs for processing 128-bit IDs

sd_id128_is_null(3) ? APIs for processing 128-bit IDs

SD_ID128_MAKE(3) ? APIs for processing 128-bit IDs

SD_ID128_MAKE_STR(3) ? APIs for processing 128-bit IDs

SD_ID128_MAKE_UUID_STR(3) ? APIs for processing 128-bit IDs

SD_ID128_NULL(3) ? APIs for processing 128-bit IDs

sd_id128_randomize(3) ? Generate 128-bit IDs

sd_id128_string_equal(3) ? APIs for processing 128-bit IDs

SD_ID128_STRING_MAX(3) ? Format or parse 128-bit IDs as strings

sd_id128_t(3) ? APIs for processing 128-bit IDs

sd_id128_to_string(3) ? Format or parse 128-bit IDs as strings

SD_ID128_TO_STRING(3) ? Format or parse 128-bit IDs as strings

sd_id128_to_uuid_string(3) ? Format or parse 128-bit IDs as strings

SD_ID128_TO_UUID_STRING(3) ? Format or parse 128-bit IDs as strings

SD_ID128_UUID_FORMAT_STR(3) ? APIs for processing 128-bit IDs

SD_ID128_UUID_STRING_MAX(3) ? Format or parse 128-bit IDs as strings

SD_INFO(3) ? APIs for new-style daemons

sd_is_fifo(3) ? Check the type of a file descriptor

sd_is_mq(3) ? Check the type of a file descriptor

sd_is_socket(3) ? Check the type of a file descriptor

sd_is_socket_inet(3) ? Check the type of a file descriptor

sd_is_socket_sockaddr(3) ? Check the type of a file descriptor

sd_is_socket_unix(3) ? Check the type of a file descriptor

sd_is_special(3) ? Check the type of a file descriptor

sd_journal(3) ? Open the system journal for reading

sd_journal_add_conjunction(3) ? Add or remove entry matches

sd_journal_add_disjunction(3) ? Add or remove entry matches

sd_journal_add_match(3) ? Add or remove entry matches

SD_JOURNAL_ALL_NAMESPACES(3) ? Open the system journal for reading

SD_JOURNAL_APPEND(3) ? Journal change notification interface

sd_journal_close(3) ? Open the system journal for reading

SD_JOURNAL_CURRENT_USER(3) ? Open the system journal for reading

sd_journal_enumerate_available_data(3) ? Read data fields from the current journal entry

sd_journal_enumerate_available_unique(3) ? Read unique data fields from the journal

sd_journal_enumerate_data(3) ? Read data fields from the current journal entry

sd_journal_enumerate_fields(3) ? Read used field names from the journal

sd_journal_enumerate_unique(3) ? Read unique data fields from the journal

sd_journal_flush_matches(3) ? Add or remove entry matches

SD_JOURNAL_FOREACH(3) ? Advance or set back the read pointer in the journal

SD_JOURNAL_FOREACH_BACKWARDS(3) ? Advance or set back the read pointer in the journal

SD_JOURNAL_FOREACH_DATA(3) ? Read data fields from the current journal

entry

SD_JOURNAL_FOREACH_FIELD(3) ? Read used field names from the journal

SD_JOURNAL_FOREACH_UNIQUE(3) ? Read unique data fields from the journal

sd_journal_get_catalog(3) ? Retrieve message catalog entry

sd_journal_get_catalog_for_message_id(3) ? Retrieve message catalog

entry

sd_journal_get_cursor(3) ? Get cursor string for or test cursor string

against the current journal entry

sd_journal_get_cutoff_monotonic_usec(3) ? Read cut-off timestamps from

the current journal entry

sd_journal_get_cutoff_realtime_usec(3) ? Read cut-off timestamps from

the current journal entry

sd_journal_get_data(3) ? Read data fields from the current journal

entry

sd_journal_get_data_threshold(3) ? Read data fields from the current

journal entry

sd_journal_get_events(3) ? Journal change notification interface

sd_journal_get_fd(3) ? Journal change notification interface

sd_journal_get_monotonic_usec(3) ? Read timestamps from the current

journal entry

sd_journal_get_realtime_usec(3) ? Read timestamps from the current

journal entry

sd_journal_get_timeout(3) ? Journal change notification interface

sd_journal_get_usage(3) ? Journal disk usage

sd_journal_has_persistent_files(3) ? Query availability of runtime or

persistent journal files

sd_journal_has_runtime_files(3) ? Query availability of runtime or

persistent journal files

SD_JOURNAL_INCLUDE_DEFAULT_NAMESPACE(3) ? Open the system journal for

reading

SD_JOURNAL_INVALIDATE(3) ? Journal change notification interface

SD_JOURNAL_LOCAL_ONLY(3) ? Open the system journal for reading

sd_journal_next(3) ? Advance or set back the read pointer in the

journal

sd_journal_next_skip(3) ? Advance or set back the read pointer in the

journal

SD_JOURNAL_NOP(3) ? Journal change notification interface

sd_journal_open(3) ? Open the system journal for reading

sd_journal_open_directory(3) ? Open the system journal for reading

sd_journal_open_directory_fd(3) ? Open the system journal for reading

sd_journal_open_files(3) ? Open the system journal for reading

sd_journal_open_files_fd(3) ? Open the system journal for reading

sd_journal_open_namespace(3) ? Open the system journal for reading

SD_JOURNAL_OS_ROOT(3) ? Open the system journal for reading

sd_journal_perror(3) ? Submit log entries to the journal

sd_journal_perror_with_location(3) ? Submit log entries to the journal

sd_journal_previous(3) ? Advance or set back the read pointer in the

journal

sd_journal_previous_skip(3) ? Advance or set back the read pointer in

the journal

sd_journal_print(3) ? Submit log entries to the journal

sd_journal_print_with_location(3) ? Submit log entries to the journal

sd_journal_printv(3) ? Submit log entries to the journal

sd_journal_printv_with_location(3) ? Submit log entries to the journal

sd_journal_process(3) ? Journal change notification interface

sd_journal_query_unique(3) ? Read unique data fields from the journal

sd_journal_reliable_fd(3) ? Journal change notification interface

sd_journal_restart_data(3) ? Read data fields from the current journal

entry

sd_journal_restart_fields(3) ? Read used field names from the journal

sd_journal_restart_unique(3) ? Read unique data fields from the journal

SD_JOURNAL_RUNTIME_ONLY(3) ? Open the system journal for reading

sd_journal_seek_cursor(3) ? Seek to a position in the journal

sd_journal_seek_head(3) ? Seek to a position in the journal

sd_journal_seek_monotonic_usec(3) ? Seek to a position in the journal

sd_journal_seek_realtime_usec(3) ? Seek to a position in the journal

sd_journal_seek_tail(3) ? Seek to a position in the journal

sd_journal_send(3) ? Submit log entries to the journal

sd_journal_send_with_location(3) ? Submit log entries to the journal

sd_journal_sendv(3) ? Submit log entries to the journal

sd_journal_sendv_with_location(3) ? Submit log entries to the journal

sd_journal_set_data_threshold(3) ? Read data fields from the current journal entry

sd_journal_stream_fd(3) ? Create log stream file descriptor to the journal

SD_JOURNAL_SUPPRESS_LOCATION(3) ? Submit log entries to the journal

SD_JOURNAL_SYSTEM(3) ? Open the system journal for reading

sd_journal_test_cursor(3) ? Get cursor string for or test cursor string against the current journal entry

sd_journal_wait(3) ? Journal change notification interface

sd_listen_fds(3) ? Check for file descriptors passed by the system manager

SD_LISTEN_FDS_START(3) ? Check for file descriptors passed by the system manager

sd_listen_fds_with_names(3) ? Check for file descriptors passed by the system manager

sd_login_monitor(3) ? Monitor login sessions, seats, users and virtual machines/containers

sd_login_monitor_flush(3) ? Monitor login sessions, seats, users and virtual machines/containers

sd_login_monitor_get_events(3) ? Monitor login sessions, seats, users and virtual machines/containers

sd_login_monitor_get_fd(3) ? Monitor login sessions, seats, users and virtual machines/containers

sd_login_monitor_get_timeout(3) ? Monitor login sessions, seats, users and virtual machines/containers

sd_login_monitor_new(3) ? Monitor login sessions, seats, users and virtual machines/containers

sd_login_monitor_unref(3) ? Monitor login sessions, seats, users and

virtual machines/containers

sd_login_monitor_unrefp(3) ? Monitor login sessions, seats, users and

virtual machines/containers

sd_machine_get_class(3) ? Determine the class and network interface

indices of a locally running virtual machine or container

sd_machine_get_ifindices(3) ? Determine the class and network interface

indices of a locally running virtual machine or container

SD_NOTICE(3) ? APIs for new-style daemons

sd_notify(3) ? Notify service manager about start-up completion and

other service status changes

sd_notify_barrier(3) ? Notify service manager about start-up completion

and other service status changes

sd_notifyf(3) ? Notify service manager about start-up completion and

other service status changes

sd_path_lookup(3) ? Query well-known file system paths

sd_path_lookup_strv(3) ? Query well-known file system paths

sd_peer_get_cgroup(3) ? Determine the owner uid of the user unit or

session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

sd_peer_get_machine_name(3) ? Determine the owner uid of the user unit

or session, or the session, user unit, system unit, container/VM or

slice that a specific PID or socket peer belongs to

sd_peer_get_owner_uid(3) ? Determine the owner uid of the user unit or

session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

sd_peer_get_session(3) ? Determine the owner uid of the user unit or

session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

sd_peer_get_slice(3) ? Determine the owner uid of the user unit or

session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

sd_peer_get_unit(3) ? Determine the owner uid of the user unit or

session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_peer_get_user_slice(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_peer_get_user_unit(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_pid_get_cgroup(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_pid_get_machine_name(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_pid_get_owner_uid(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_pid_get_session(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_pid_get_slice(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_pid_get_unit(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_pid_get_user_slice(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_pid_get_user_unit(3)` ? Determine the owner uid of the user unit or session, or the session, user unit, system unit, container/VM or slice

that a specific PID or socket peer belongs to

`sd_pid_notify(3)` ? Notify service manager about start-up completion and other service status changes

sd_pid_notify_with_fds(3) ? Notify service manager about start-up completion and other service status changes

sd_pid_notifyf(3) ? Notify service manager about start-up completion and other service status changes

sd_seat_can_graphical(3) ? Determine state of a specific seat

sd_seat_can_tty(3) ? Determine state of a specific seat

sd_seat_get_active(3) ? Determine state of a specific seat

sd_seat_get_sessions(3) ? Determine state of a specific seat

sd_session_get_class(3) ? Determine state of a specific session

sd_session_get_desktop(3) ? Determine state of a specific session

sd_session_get_display(3) ? Determine state of a specific session

sd_session_get_remote_host(3) ? Determine state of a specific session

sd_session_get_remote_user(3) ? Determine state of a specific session

sd_session_get_seat(3) ? Determine state of a specific session

sd_session_get_service(3) ? Determine state of a specific session

sd_session_get_state(3) ? Determine state of a specific session

sd_session_get_tty(3) ? Determine state of a specific session

sd_session_get_type(3) ? Determine state of a specific session

sd_session_get_uid(3) ? Determine state of a specific session

sd_session_get_vt(3) ? Determine state of a specific session

sd_session_is_active(3) ? Determine state of a specific session

sd_session_is_remote(3) ? Determine state of a specific session

sd_uid_get_display(3) ? Determine login state of a specific Unix user ID

sd_uid_get_seats(3) ? Determine login state of a specific Unix user ID

sd_uid_get_sessions(3) ? Determine login state of a specific Unix user ID

sd_uid_get_state(3) ? Determine login state of a specific Unix user ID

sd_uid_is_on_seat(3) ? Determine login state of a specific Unix user ID

SD_WARNING(3) ? APIs for new-style daemons

sd_watchdog_enabled(3) ? Check whether the service manager expects watchdog keep-alive notifications from a service

shutdown(8) ? Halt, power off or reboot the machine

sleep.conf.d(5) ? Suspend and hibernation configuration file

sysctl.d(5) ? Configure kernel parameters at boot

system.conf.d(5) ? System and session service manager configuration files

systemctl(1) ? Control the systemd system and service manager

systemd(1) ? systemd system and service manager

systemd-analyze(1) ? Analyze and debug system manager

systemd-ask-password(1) ? Query the user for a system password

systemd-ask-password-console.path(8) ? Query the user for system passwords on the console and via wall

systemd-ask-password-console.service(8) ? Query the user for system passwords on the console and via wall

systemd-ask-password-wall.path(8) ? Query the user for system passwords on the console and via wall

systemd-ask-password-wall.service(8) ? Query the user for system passwords on the console and via wall

systemd-backlight(8) ? Load and save the display backlight brightness at boot and shutdown

systemd-backlight@.service(8) ? Load and save the display backlight brightness at boot and shutdown

systemd-binfmt(8) ? Configure additional binary formats for executables at boot

systemd-binfmt.service(8) ? Configure additional binary formats for executables at boot

systemd-bless-boot(8) ? Mark current boot process as successful

systemd-bless-boot-generator(8) ? Pull systemd-bless-boot.service into the initial boot transaction when boot counting is in effect

systemd-bless-boot.service(8) ? Mark current boot process as successful

systemd-boot(7) ? A simple UEFI boot manager

systemd-boot-check-no-failures(8) ? verify that the system booted up cleanly

systemd-boot-check-no-failures.service(8) ? verify that the system booted up cleanly

systemd-boot-system-token.service(8) ? Generate an initial boot loader system token and random seed

systemd-cat(1) ? Connect a pipeline or program's output with the journal

systemd-cgls(1) ? Recursively show control group contents

systemd-cgtop(1) ? Show top control groups by their resource usage

systemd-coredump(8) ? Acquire, save and process core dumps

systemd-coredump.socket(8) ? Acquire, save and process core dumps

systemd-coredump@.service(8) ? Acquire, save and process core dumps

systemd-creds(1) ? Lists, shows, encrypts and decrypts service credentials

systemd-cryptenroll(1) ? Enroll PKCS#11, FIDO2, TPM2 token/devices to LUKS2 encrypted volumes

systemd-cryptsetup(8) ? Full disk decryption logic

systemd-cryptsetup-generator(8) ? Unit generator for /etc/crypttab

systemd-cryptsetup@.service(8) ? Full disk decryption logic

systemd-debug-generator(8) ? Generator for enabling a runtime debug shell and masking specific units at boot

systemd-delta(1) ? Find overridden configuration files

systemd-detect-virt(1) ? Detect execution in a virtualized environment

systemd-dissect(1) ? Dissect Discoverable Disk Images (DDIs)

systemd-environment-d-generator(8) ? Load variables specified by environment.d

systemd-escape(1) ? Escape strings for usage in systemd unit names

systemd-firstboot(1) ? Initialize basic system settings on or before the first boot-up of a system

systemd-firstboot.service(1) ? Initialize basic system settings on or before the first boot-up of a system

systemd-fsck(8) ? File system checker logic

systemd-fsck-root.service(8) ? File system checker logic

systemd-fsck@.service(8) ? File system checker logic

systemd-fstab-generator(8) ? Unit generator for /etc/fstab

systemd-getty-generator(8) ? Generator for enabling getty instances on

the console

systemd-gpt-auto-generator(8) ? Generator for automatically discovering and mounting root, /home/ , /srv/ , /var/ and /var/tmp/ partitions, as well as discovering and enabling swap partitions, based on GPT partition type GUIDs

systemd-growfs(8) ? Creating and growing file systems on demand

systemd-growfs@.service(8) ? Creating and growing file systems on demand

systemd-halt.service(8) ? System shutdown logic

systemd-hibernate-resume(8) ? Resume from hibernation

systemd-hibernate-resume-generator(8) ? Unit generator for resume= kernel parameter

systemd-hibernate-resume@.service(8) ? Resume from hibernation

systemd-hibernate.service(8) ? System sleep state logic

systemd-hostnamed(8) ? Daemon to control system hostname from programs

systemd-hostnamed.service(8) ? Daemon to control system hostname from programs

systemd-hwdb(8) ? hardware database management tool

systemd-hybrid-sleep.service(8) ? System sleep state logic

systemd-id128(1) ? Generate and print sd-128 identifiers

systemd-importd(8) ? VM and container image import and export service

systemd-importd.service(8) ? VM and container image import and export service

systemd-inhibit(1) ? Execute a program with an inhibition lock taken

systemd-initctl(8) ? /dev/initctl compatibility

systemd-initctl.service(8) ? /dev/initctl compatibility

systemd-initctl.socket(8) ? /dev/initctl compatibility

systemd-integritysetup(8) ? Disk integrity protection logic

systemd-integritysetup-generator(8) ? Unit generator for integrity protected block devices

systemd-integritysetup@.service(8) ? Disk integrity protection logic

systemd-journal-gatewayd(8) ? HTTP server for journal events

systemd-journal-gatewayd.service(8) ? HTTP server for journal events

systemd-journal-gatewayd.socket(8) ? HTTP server for journal events

systemd-journal-remote(8) ? Receive journal messages over the network

systemd-journal-remote.service(8) ? Receive journal messages over the network

systemd-journal-remote.socket(8) ? Receive journal messages over the network

systemd-journal-upload(8) ? Send journal messages over the network

systemd-journal-upload.service(8) ? Send journal messages over the network

systemd-journal(8) ? Journal service

systemd-journal-audit.socket(8) ? Journal service

systemd-journal-dev-log.socket(8) ? Journal service

systemd-journal-varlink@.socket(8) ? Journal service

systemd-journal.service(8) ? Journal service

systemd-journal.socket(8) ? Journal service

systemd-journal@.service(8) ? Journal service

systemd-journal@.socket(8) ? Journal service

systemd-kexec.service(8) ? System shutdown logic

systemd-localed(8) ? Locale bus mechanism

systemd-localed.service(8) ? Locale bus mechanism

systemd-logind(8) ? Login manager

systemd-logind.service(8) ? Login manager

systemd-machine-id-commit.service(8) ? Commit a transient machine ID to disk

systemd-machine-id-setup(1) ? Initialize the machine ID in /etc/machine-id

systemd-machined(8) ? Virtual machine and container registration manager

systemd-machined.service(8) ? Virtual machine and container registration manager

systemd-makefs(8) ? Creating and growing file systems on demand

systemd-makefs@.service(8) ? Creating and growing file systems on demand

systemd-measure(1) ? Pre-calculate and sign expected TPM2 PCR values for booted unified kernel images

systemd-mkswap@.service(8) ? Creating and growing file systems on demand

systemd-modules-load(8) ? Load kernel modules at boot

systemd-modules-load.service(8) ? Load kernel modules at boot

systemd-mount(1) ? Establish and destroy transient mount or auto-mount points

systemd-network-generator(8) ? Generate network configuration from the kernel command line

systemd-network-generator.service(8) ? Generate network configuration from the kernel command line

systemd-notify(1) ? Notify service manager about start-up completion and other daemon status changes

systemd-nspawn(1) ? Spawn a command or OS in a light-weight container

systemd-oomd(8) ? A userspace out-of-memory (OOM) killer

systemd-oomd.service(8) ? A userspace out-of-memory (OOM) killer

systemd-path(1) ? List and query system and user paths

systemd-pcrphase(8) ? Measure boot phase into TPM2 PCR 11

systemd-pcrphase-initrd.service(8) ? Measure boot phase into TPM2 PCR 11

systemd-pcrphase-sysinit.service(8) ? Measure boot phase into TPM2 PCR 11

systemd-pcrphase.service(8) ? Measure boot phase into TPM2 PCR 11

systemd-poweroff.service(8) ? System shutdown logic

systemd-pstore(8) ? A service to archive contents of pstore

systemd-pstore.service(8) ? A service to archive contents of pstore

systemd-quotacheck(8) ? File system quota checker logic

systemd-quotacheck.service(8) ? File system quota checker logic

systemd-random-seed(8) ? Load and save the system random seed at boot and shutdown

systemd-random-seed.service(8) ? Load and save the system random seed at boot and shutdown

systemd-rc-local-generator(8) ? Compatibility generator and service to start /etc/rc.d/rc.local during boot

systemd-reboot.service(8) ? System shutdown logic

systemd-remount-fs(8) ? Remount root and kernel file systems

systemd-remount-fs.service(8) ? Remount root and kernel file systems

systemd-repart(8) ? Automatically grow and add partitions

systemd-repart.service(8) ? Automatically grow and add partitions

systemd-resolved(8) ? Network Name Resolution manager

systemd-resolved.service(8) ? Network Name Resolution manager

systemd-rfkill(8) ? Load and save the RF kill switch state at boot and change

systemd-rfkill.service(8) ? Load and save the RF kill switch state at boot and change

systemd-rfkill.socket(8) ? Load and save the RF kill switch state at boot and change

systemd-run(1) ? Run programs in transient scope units, service units, or path-, socket-, or timer-triggered service units

systemd-run-generator(8) ? Generator for invoking commands specified on the kernel command line as system service

systemd-shutdown(8) ? System shutdown logic

systemd-sleep(8) ? System sleep state logic

systemd-sleep.conf(5) ? Suspend and hibernation configuration file

systemd-socket-activate(1) ? Test socket activation of daemons

systemd-socket-proxyd(8) ? Bidirectionally proxy local sockets to another (possibly remote) socket

systemd-stdio-bridge(1) ? D-Bus proxy

systemd-stub(7) ? A simple UEFI kernel boot stub

systemd-suspend-then-hibernate.service(8) ? System sleep state logic

systemd-suspend.service(8) ? System sleep state logic

systemd-sysctl(8) ? Configure kernel parameters at boot

systemd-sysctl.service(8) ? Configure kernel parameters at boot

systemd-sysext(8) ? Activates System Extension Images

systemd-sysext.service(8) ? Activates System Extension Images

systemd-system-update-generator(8) ? Generator for redirecting boot to offline update mode

systemd-system.conf(5) ? System and session service manager configuration files

systemd-sysupdate(8) ? Automatically Update OS or Other Resources

systemd-sysupdate-reboot.service(8) ? Automatically Update OS or Other Resources

systemd-sysupdate-reboot.timer(8) ? Automatically Update OS or Other Resources

systemd-sysupdate.service(8) ? Automatically Update OS or Other Resources

systemd-sysupdate.timer(8) ? Automatically Update OS or Other Resources

systemd-sysusers(8) ? Allocate system users and groups

systemd-sysusers.service(8) ? Allocate system users and groups

systemd-sysv-generator(8) ? Unit generator for SysV init scripts

systemd-timedated(8) ? Time and date bus mechanism

systemd-timedated.service(8) ? Time and date bus mechanism

systemd-tmpfiles(8) ? Creates, deletes and cleans up volatile and temporary files and directories

systemd-tmpfiles-clean.service(8) ? Creates, deletes and cleans up volatile and temporary files and directories

systemd-tmpfiles-clean.timer(8) ? Creates, deletes and cleans up volatile and temporary files and directories

systemd-tmpfiles-setup-dev.service(8) ? Creates, deletes and cleans up volatile and temporary files and directories

systemd-tmpfiles-setup.service(8) ? Creates, deletes and cleans up volatile and temporary files and directories

systemd-tty-ask-password-agent(1) ? List or process pending systemd password requests

systemd-udev-settle.service(8) ? Wait for all pending udev events to be handled

systemd-udev(8) ? Device event managing daemon

systemd-udev-control.socket(8) ? Device event managing daemon

systemd-udev-kernel.socket(8) ? Device event managing daemon

systemd-udev.service(8) ? Device event managing daemon

systemd-umount(1) ? Establish and destroy transient mount or auto-mount points

systemd-update-done(8) ? Mark /etc/ and /var/ fully updated

systemd-update-done.service(8) ? Mark /etc/ and /var/ fully updated

systemd-update-utmp(8) ? Write audit and utmp updates at bootup, runlevel changes and shutdown

systemd-update-utmp-runlevel.service(8) ? Write audit and utmp updates at bootup, runlevel changes and shutdown

systemd-update-utmp.service(8) ? Write audit and utmp updates at bootup, runlevel changes and shutdown

systemd-user-runtime-dir(5) ? System units to start the user manager

systemd-user-sessions(8) ? Permit user logins after boot, prohibit user logins at shutdown

systemd-user-sessions.service(8) ? Permit user logins after boot, prohibit user logins at shutdown

systemd-user.conf(5) ? System and session service manager configuration files

systemd-vconsole-setup(8) ? Configure the virtual consoles

systemd-vconsole-setup.service(8) ? Configure the virtual consoles

systemd-veritysetup(8) ? Disk verity protection logic

systemd-veritysetup-generator(8) ? Unit generator for verity protected block devices

systemd-veritysetup@.service(8) ? Disk verity protection logic

systemd-volatile-root(8) ? Make the root file system volatile

systemd-volatile-root.service(8) ? Make the root file system volatile

systemd-xdg-autostart-generator(8) ? User unit generator for XDG autostart files

systemd.automount(5) ? Automount unit configuration

systemd.device(5) ? Device unit configuration

systemd.directives(7) ? Index of configuration directives

systemd.dnssd(5) ? DNS-SD configuration

systemd.environment-generator(7) ? systemd environment file generators

systemd.exec(5) ? Execution environment configuration

systemd.generator(7) ? systemd unit generators

systemd.journal-fields(7) ? Special journal fields

systemd.kill(5) ? Process killing procedure configuration

systemd.link(5) ? Network device configuration

systemd.mount(5) ? Mount unit configuration

systemd.negative(5) ? DNSSEC trust anchor configuration files

systemd.net-naming-scheme(7) ? Network device naming schemes

systemd.nspawn(5) ? Container settings

systemd.offline-updates(7) ? Implementation of offline updates in
systemd

systemd.path(5) ? Path unit configuration

systemd.positive(5) ? DNSSEC trust anchor configuration files

systemd.preset(5) ? Service enablement presets

systemd.resource-control(5) ? Resource control unit settings

systemd.scope(5) ? Scope unit configuration

systemd.service(5) ? Service unit configuration

systemd.slice(5) ? Slice unit configuration

systemd.socket(5) ? Socket unit configuration

systemd.special(7) ? Special systemd units

systemd.swap(5) ? Swap unit configuration

systemd.syntax(7) ? General syntax of systemd configuration files

systemd.system-credentials(7) ? System Credentials

systemd.target(5) ? Target unit configuration

systemd.time(7) ? Time and date specifications

systemd.timer(5) ? Timer unit configuration

systemd.unit(5) ? Unit configuration

sysupdate.d(5) ? Transfer Definition Files for Automatic Updates

sysusers.d(5) ? Declarative allocation of system users and groups

T

telinit(8) ? Change SysV runlevel

timedatectl(1) ? Control the system time and date

tmpfiles.d(5) ? Configuration for creation, deletion and cleaning of volatile and temporary files

U

udev(7) ? Dynamic device management

udev.conf(5) ? Configuration for device event managing daemon

udev_device_get_action(3) ? Query device properties

udev_device_get_current_tags_list_entry(3) ? Retrieve or set device attributes

udev_device_get_devlinks_list_entry(3) ? Retrieve or set device attributes

udev_device_get_devnode(3) ? Query device properties

udev_device_get_devnum(3) ? Query device properties

udev_device_get_devpath(3) ? Query device properties

udev_device_get_devtype(3) ? Query device properties

udev_device_get_driver(3) ? Query device properties

udev_device_get_is_initialized(3) ? Query device properties

udev_device_get_parent(3) ? Query device properties

udev_device_get_parent_with_subsystem_devtype(3) ? Query device properties

udev_device_get_properties_list_entry(3) ? Retrieve or set device attributes

udev_device_get_property_value(3) ? Retrieve or set device attributes

udev_device_get_subsystem(3) ? Query device properties

udev_device_get_sysattr_list_entry(3) ? Retrieve or set device attributes

udev_device_get_sysattr_value(3) ? Retrieve or set device attributes

udev_device_get_sysname(3) ? Query device properties

udev_device_get_sysnum(3) ? Query device properties

udev_device_get_syspath(3) ? Query device properties

udev_device_get_tags_list_entry(3) ? Retrieve or set device attributes

udev_device_get_udev(3) ? Query device properties

udev_device_has_current_tag(3) ? Retrieve or set device attributes

udev_device_has_tag(3) ? Retrieve or set device attributes

udev_device_new_from_device_id(3) ? Create, acquire and release a udev device object

udev_device_new_from_devnum(3) ? Create, acquire and release a udev device object

udev_device_new_from_environment(3) ? Create, acquire and release a udev device object

udev_device_new_from_subsystem_sysname(3) ? Create, acquire and release a udev device object

udev_device_new_from_syspath(3) ? Create, acquire and release a udev device object

udev_device_ref(3) ? Create, acquire and release a udev device object

udev_device_set_sysattr_value(3) ? Retrieve or set device attributes

udev_device_unref(3) ? Create, acquire and release a udev device object

udev_enumerate_add_match_is_initialized(3) ? Modify filters

udev_enumerate_add_match_parent(3) ? Modify filters

udev_enumerate_add_match_property(3) ? Modify filters

udev_enumerate_add_match_subsystem(3) ? Modify filters

udev_enumerate_add_match_sysattr(3) ? Modify filters

udev_enumerate_add_match_sysname(3) ? Modify filters

udev_enumerate_add_match_tag(3) ? Modify filters

udev_enumerate_add_nomatch_subsystem(3) ? Modify filters

udev_enumerate_add_nomatch_sysattr(3) ? Modify filters

udev_enumerate_add_syspath(3) ? Query or modify a udev enumerate object

udev_enumerate_get_list_entry(3) ? Query or modify a udev enumerate object

udev_enumerate_get_udev(3) ? Query or modify a udev enumerate object

udev_enumerate_new(3) ? Create, acquire and release a udev enumerate object

udev_enumerate_ref(3) ? Create, acquire and release a udev enumerate object

udev_enumerate_scan_devices(3) ? Query or modify a udev enumerate object

udev_enumerate_scan_subsystems(3) ? Query or modify a udev enumerate

object

udev_enumerate_unref(3) ? Create, acquire and release a udev enumerate

object

udev_list_entry(3) ? Iterate and access udev lists

udev_list_entry_get_by_name(3) ? Iterate and access udev lists

udev_list_entry_get_name(3) ? Iterate and access udev lists

udev_list_entry_get_next(3) ? Iterate and access udev lists

udev_list_entry_get_value(3) ? Iterate and access udev lists

udev_monitor_enable_receiving(3) ? Query and modify device monitor

udev_monitor_filter_add_match_subsystem_devtype(3) ? Modify filters

udev_monitor_filter_add_match_tag(3) ? Modify filters

udev_monitor_filter_remove(3) ? Modify filters

udev_monitor_filter_update(3) ? Modify filters

udev_monitor_get_fd(3) ? Query and modify device monitor

udev_monitor_get_udev(3) ? Query and modify device monitor

udev_monitor_new_from_netlink(3) ? Create, acquire and release a udev

monitor object

udev_monitor_receive_device(3) ? Query and modify device monitor

udev_monitor_ref(3) ? Create, acquire and release a udev monitor object

udev_monitor_set_receive_buffer_size(3) ? Query and modify device

monitor

udev_monitor_unref(3) ? Create, acquire and release a udev monitor

object

udev_new(3) ? Create, acquire and release a udev context object

udev_ref(3) ? Create, acquire and release a udev context object

udev_unref(3) ? Create, acquire and release a udev context object

udevadm(8) ? udev management tool

user-runtime-dir@.service(5) ? System units to start the user manager

user.conf.d(5) ? System and session service manager configuration files

user@.service(5) ? System units to start the user manager

V

vconsole.conf(5) ? Configuration file for the virtual console

veritytab(5) ? Configuration for verity block devices

SEE ALSO

systemd.directives(7)

This index contains 1058 entries, referring to 359 individual manual pages.

systemd 252

SYSTEMD.INDEX(7)