



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'tmpnam_r.3'

\$ man tmpnam_r.3

TMPNAM(3) Linux Programmer's Manual TMPNAM(3)

NAME

tmpnam, tmpnam_r - create a name for a temporary file

SYNOPSIS

```
#include <stdio.h>
```

```
char *tmpnam(char *s);
```

```
char *tmpnam_r(char *s);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
tmpnam_r()
```

Since glibc 2.19:

```
  _DEFAULT_SOURCE
```

Up to and including glibc 2.19:

```
  _BSD_SOURCE || _SVID_SOURCE
```

DESCRIPTION

Note: avoid using these functions; use mkstemp(3) or tmpfile(3) instead.

The tmpnam() function returns a pointer to a string that is a valid filename, and such that a file with this name did not exist at some

point in time, so that naive programmers may think it a suitable name for a temporary file. If the argument s is NULL, this name is generated in an internal static buffer and may be overwritten by the next call to tmpnam(). If s is not NULL, the name is copied to the character array (of length at least L_tmpnam) pointed to by s and the value s is returned in case of success.

The created pathname has a directory prefix P_tmpdir. (Both L_tmpnam and P_tmpdir are defined in <stdio.h>, just like the TMP_MAX mentioned below.)

The tmpnam_r() function performs the same task as tmpnam(), but returns NULL (to indicate an error) if s is NULL.

RETURN VALUE

These functions return a pointer to a unique temporary filename, or NULL if a unique name cannot be generated.

ERRORS

No errors are defined.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?tmpnam() ? Thread safety ? MT-Unsafe race:tmpnam!/s ?

??

?tmpnam_r() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

tmpnam(): SVr4, 4.3BSD, C89, C99, POSIX.1-2001. POSIX.1-2008 marks tmpnam() as obsolete.

tmpnam_r() is a nonstandard extension that is also available on a few other systems.

NOTES

The tmpnam() function generates a different string each time it is

called, up to TMP_MAX times. If it is called more than TMP_MAX times, the behavior is implementation defined.

Although these functions generate names that are difficult to guess, it is nevertheless possible that between the time that the pathname is re? turned and the time that the program opens it, another program might create that pathname using open(2), or create it as a symbolic link.

This can lead to security holes. To avoid such possibilities, use the open(2) O_EXCL flag to open the pathname. Or better yet, use mkstemp(3) or tmpfile(3).

Portable applications that use threads cannot call tmpnam() with a NULL argument if either _POSIX_THREADS or _POSIX_THREAD_SAFE_FUNCTIONS is defined.

BUGS

Never use these functions. Use mkstemp(3) or tmpfile(3) instead.

SEE ALSO

mkstemp(3), mktemp(3), tmpnam(3), tmpfile(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

TMPNAM(3)