



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'tracer.8'

\$ man tracer.8

TRACER(8) Tracer TRACER(8)

NAME

tracer - finds outdated running applications in your system

DESCRIPTION

Tracer determines which applications use outdated files and prints them. For special kind of applications such as services or daemons, it suggests a standard command to restart it. Detecting whether file is outdated or not is based on a simple idea. If application has loaded in memory any version of a file which is provided by any package updated since system was booted up, tracer consider this application as out? dated.

OPTIONS

GENERAL

- version print program version
- h, --help show this help message and exit
- q, --quiet do not print additional information
- v, --verbose print more informations. Use -v or -vv

MODES

--helpers not list applications, but list their helpers

-i, --interactive run tracer in interactive mode. Print numbered applications and give helpers based on numbers

-s app_name [app_name ...], --show app_name [app_name ...] show helper for given application

-a, --all list even session and unrestartable applications

--daemons-only, --services-only list only daemons/services

--hooks-only do not print traced applications, only run their hooks

-t TIMESTAMP, --timestamp TIMESTAMP since when the updates should be

-n, --now when there are specified packages, dont look for time of their update. Use "now" instead

USERS

-u username, --user username

-r, --root

-e, --everyone

DEBUG

--show-resource=<option>

options: packages | processes | rules | applications | system

dump informations that tracer can use

EXIT CODES

Status codes and their meanings:

```

+-----+-----+
| Status code | Meaning          |
+=====+=====+
| 1-99      | Error exit codes  |
+-----+-----+
| 0         | No affected applications |
+-----+-----+
| 101      | Found some affected applications |
+-----+-----+
| 102      | Found some affected daemons   |

```

```
+-----+-----+
| 103   | Session restart needed   |
+-----+-----+
| 104   | Reboot needed           |
+-----+-----+
```

EXAMPLES

Show your applications which needs restarting (basic usage)

```
tracer
```

Show informations about application

```
tracer --show mysqld
```

Show even affected files of the application

```
tracer --show mysqld -vv
```

In interactive mode show all applications modified only through packages changed since timestamp

```
tracer -iat 1414248388.04
```

AUTHOR

FrostyX <frostyx@email.cz>

COPYRIGHT

2021, FrostyX

recent

Aug 10, 2021

TRACER(8)