



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'tty.4'

\$ man tty.4

TTY(4) Linux Programmer's Manual TTY(4)

NAME

 tty - controlling terminal

DESCRIPTION

 The file `/dev/tty` is a character file with major number 5 and minor number 0, usually with mode 0666 and ownership root:tty. It is a synonym for the controlling terminal of a process, if any.

 In addition to the `ioctl(2)` requests supported by the device that `tty` refers to, the `ioctl(2)` request `TIOCNOTTY` is supported.

TIOCNOTTY

 Detach the calling process from its controlling terminal.

 If the process is the session leader, then `SIGHUP` and `SIGCONT` signals are sent to the foreground process group and all processes in the current session lose their controlling `tty`.

 This `ioctl(2)` call works only on file descriptors connected to `/dev/tty`. It is used by daemon processes when they are invoked by a user at a terminal. The process attempts to open `/dev/tty`. If the open succeeds, it detaches itself from the terminal by using `TIOCNOTTY`,

while if the open fails, it is obviously not attached to a terminal and does not need to detach itself.

FILES

/dev/tty

SEE ALSO

chown(1), mknod(1), ioctl(2), ioctl_console(2), ioctl_tty(2),
termios(3), ttyS(4), vcs(4), pty(7), agetty(8), mingetty(8)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2019-03-06

TTY(4)