



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ttyS.4'

\$ man ttyS.4

TTYs(4) Linux Programmer's Manual TTYs(4)

NAME

 ttyS - serial terminal lines

DESCRIPTION

 ttyS[0-3] are character devices for the serial terminal lines.

 They are typically created by:

```
    mknod -m 660 /dev/ttyS0 c 4 64 # base address 0x3f8
```

```
    mknod -m 660 /dev/ttyS1 c 4 65 # base address 0x2f8
```

```
    mknod -m 660 /dev/ttyS2 c 4 66 # base address 0x3e8
```

```
    mknod -m 660 /dev/ttyS3 c 4 67 # base address 0x2e8
```

```
    chown root:tty /dev/ttyS[0-3]
```

FILES

 /dev/ttyS[0-3]

SEE ALSO

 chown(1), mknod(1), tty(4),agetty(8), mingetty(8), setserial(8)

COLOPHON

 This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the

latest version of this page, can be found at

<https://www.kernel.org/doc/man-pages/>.

Linux

1992-12-19

TTY(4)