



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'udisks2.conf.5'

\$ man udisks2.conf.5

UDISKS2.CONF(5) UDisks Daemon Configuration UDISKS2.CONF(5)

NAME

udisks2.conf - The udisks2 configuration file

DESCRIPTION

The udisks project provides additional functionality via pluggable modules. These plugins can be inserted into the daemon either by D-Bus call org.freedesktop.UDisks2.Manager.EnableModules() or by running the udisks daemon with --force-load-modules command line option.

It is also possible to configure the modules loading behavior via the configuration file placed at /etc/udisks2/udisks2.conf.

CONFIGURATION FILE

The default configuration file udisks2.conf looks like this:

```
[udisks2]
modules=*
modules_load_preference=ondemand
[defaults]
encryption=luks1
modules = <string list>
```

This variable controls what modules should be loaded. It may contain either a comma-separated list of modules to load or a single asterisk which stands for all the modules.

modules_load_preference = ondemand|onstartup

This key tells udisksd when to load the plugins: either at startup or on demand by D-Bus

org.freedesktop.UDisks2.Manager.EnableModules().

encryption = luks1|luks2

This variable controls which encryption technology will be used by default when creating an encrypted filesystem.

AUTHOR

<phatina@redhat.com>

BUGS

Please send bug reports to either the distribution bug tracker or the upstream bug tracker at

<https://github.com/storaged-project/udisks/issues>.

SEE ALSO

udisks(8), udisksctl(1), umount.udisks2(8)

udisks2.conf 2.9.4

August 2018

UDISKS2.CONF(5)