

Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ul.1'

## \$ man ul.1

UL(1)

UL(1)

### NAME

ul - do underlining

### SYNOPSIS

ul [options] [file...]

### DESCRIPTION

ul reads the named files (or standard input if none are given) and translates occurrences of underscores to the sequence which indicates underlining for the terminal in use, as specified by the environment variable TERM. The terminfo database is read to determine the appropriate sequences for underlining. If the terminal is incapable of underlining but is capable of a standout mode, then that is used instead. If the terminal can overstrike, or handles underlining automatically, ul degenerates to cat(1). If the terminal cannot underline, underlining is ignored.

User Commands

### OPTIONS

-i, --indicated

Underlining is indicated by a separate line containing appropriate

dashes `-'; this is useful when you want to look at the underlining

which is present in an nroff output stream on a crt-terminal.

#### -t, -T, --terminal terminal

Override the environment variable TERM with the specified terminal

type.

#### -V, --version

Display version information and exit.

-h, --help

Display help text and exit.

## ENVIRONMENT

The following environment variable is used:

## TERM

The TERM variable is used to relate a tty device with its device

capability description (see terminfo(5)). TERM is set at login

time, either by the default terminal type specified in /etc/ttys or

as set during the login process by the user in their login file

(see setenv(3)).

### HISTORY

The ul command appeared in 3.0BSD.

### BUGS

nroff usually outputs a series of backspaces and underlines intermixed

with the text to indicate underlining. No attempt is made to optimize

the backward motion.

### SEE ALSO

colcrt(1), login(1), man(1), nroff(1), setenv(3), terminfo(5)

# REPORTING BUGS

For bug reports, use the issue tracker at

https://github.com/karelzak/util-linux/issues.

### AVAILABILITY

The ul command is part of the util-linux package which can be

UL(1)

downloaded from Linux Kernel Archive

<https://www.kernel.org/pub/linux/utils/util-linux/>.