



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'unlockpt.3'

\$ man unlockpt.3

UNLOCKPT(3) Linux Programmer's Manual UNLOCKPT(3)

NAME

unlockpt - unlock a pseudoterminal master/slave pair

SYNOPSIS

```
#define _XOPEN_SOURCE
```

```
#include <stdlib.h>
```

```
int unlockpt(int fd);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
unlockpt():
```

Since glibc 2.24:

```
_XOPEN_SOURCE >= 500 ||
```

```
(_XOPEN_SOURCE && _XOPEN_SOURCE_EXTENDED)
```

Glibc 2.23 and earlier:

```
_XOPEN_SOURCE
```

DESCRIPTION

The unlockpt() function unlocks the slave pseudoterminal device corre?

sponding to the master pseudoterminal referred to by the file descrip?

tor fd.

unlockpt() should be called before opening the slave side of a pseu?
doterminal.

RETURN VALUE

When successful, unlockpt() returns 0. Otherwise, it returns -1 and sets errno appropriately.

ERRORS

EBADF The fd argument is not a file descriptor open for writing.

EINVAL The fd argument is not associated with a master pseudoterminal.

VERSIONS

unlockpt() is provided in glibc since version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see at?
tributes(7).

??

?Interface ? Attribute ? Value ?

??

?unlockpt() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

SEE ALSO

grantpt(3), posix_openpt(3), ptsname(3), pts(4), pty(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.