



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'wcscspn.3'***

***\$ man wcscspn.3***

WCSCSPN(3)           Linux Programmer's Manual           WCSCSPN(3)

#### NAME

wcscspn - search a wide-character string for any of a set of wide characters

#### SYNOPSIS

```
#include <wchar.h>

size_t wcscspn(const wchar_t *wcs, const wchar_t *reject);
```

#### DESCRIPTION

The wcscspn() function is the wide-character equivalent of the strcspn(3) function. It determines the length of the longest initial segment of wcs which consists entirely of wide-characters not listed in reject. In other words, it searches for the first occurrence in the wide-character string wcs of any of the characters in the wide-character string reject.

#### RETURN VALUE

The wcscspn() function returns the number of wide characters in the longest initial segment of wcs which consists entirely of wide-characters not listed in reject. In other words, it returns the position of

the first occurrence in the wide-character string `wcs` of any of the characters in the wide-character string `reject`, or `wcslen(wcs)` if there is none.

## ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

??

?Interface ? Attribute ? Value ?

??

?wscspn() ? Thread safety ? MT-Safe ?

??

## CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

## SEE ALSO

[strcspn\(3\)](#), [wcpbrk\(3\)](#), [wcspn\(3\)](#)

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU                      2015-08-08                      WCSCSPN(3)