



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'wmemmove.3'

\$ man wmemmove.3

WMEMMOVE(3) Linux Programmer's Manual WMEMMOVE(3)

NAME

wmemmove - copy an array of wide-characters

SYNOPSIS

```
#include <wchar.h>

wchar_t *wmemmove(wchar_t *dest, const wchar_t *src, size_t n);
```

DESCRIPTION

The wmemmove() function is the wide-character equivalent of the memmove(3) function. It copies n wide characters from the array starting at src to the array starting at dest. The arrays may overlap.

The programmer must ensure that there is room for at least n wide characters at dest.

RETURN VALUE

wmemmove() returns dest.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

????????????????????????????????????????????????????????

?Interface ? Attribute ? Value ?

????????????????????????????????????????????????????????????

?wmemmove() ? Thread safety ? MT-Safe ?

????????????????????????????????????????????????????????????

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

memmove(3), wmemcpy(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU 2015-08-08 WMEMMOVE(3)