



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'wvgain.1'

\$ man wvgain.1

WVGAIN(1) WavPack Executable Programs WVGAIN(1)

NAME

wvgain - adds ReplayGain information to wavpack files

SYNOPSIS

wvgain [-options] INFILE...

DESCRIPTION

wvgain perceptually analyzes WavPack audio files for volume, calculates ReplayGain information based on this, and adds the appropriate APEv2 tag fields. ReplayGain-enabled players will use this information to produce the same perceived loudness on all tracks. Both individual track and whole album ReplayGain information can be calculated.

OPTIONS

- a
album mode (all files scanned are considered an album)
- c
clean ReplayGain values from all files
- d
display calculated values only (no files are modified)

- i
ignore .wvc file (forces hybrid lossy)
- n
new files only (skip files with track info, or album info if album mode specified)
- q
quiet (keep console output to a minimum)
- s
show stored values only (no analysis)
- v
write program version to stdout
- z[n]
don't set (n = 0 or omitted) or set (n = 1) console title to indicate progress (leaves "WvGain Completed")

SEE ALSO

wavpack(1), wvunpack(1), wvtag(1)

Please visit www.wavpack.com for more information

COPYRIGHT

This manual page was written by Sebastian Dröge <slomo@debian.org> and David Bryant <david@wavpack.com>. Permission is granted to copy, distribute and/or modify this document under the terms of the BSD License.

AUTHORS

Sebastian Dröge <slomo@debian.org>

Original author

David Bryant <david@wavpack.com>

Updates

COPYRIGHT

Copyright ? 2005 Sebastian Dröge

Copyright ? 2021 David Bryant

WavPack 5.4.0

2021-01-10

WVGAIN(1)