



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'xdg-user-dirs-update.1'***

***\$ man xdg-user-dirs-update.1***

XDG-USER-DIRS-UPD(1)      User Commands      XDG-USER-DIRS-UPD(1)

NAME

xdg-user-dirs-update - Update XDG user dir configuration

SYNOPSIS

xdg-user-dirs-update [OPTION...] [--set NAME PATH...]

DESCRIPTION

xdg-user-dirs-update updates the current state of the users

user-dirs.dir. If none existed before then one is created based on the

system default values, or falling back to the old non-translated

filenames if such directories exists. The list of old directories used

are: ~/Desktop, ~/Templates and ~/Public.

If an old configuration exists it is updated with any new default

directories. Additionally, any configured directories that point to

non-existing locations are reset by pointing then to the users home

directory. This typically happens when the users removed the directory,

so they likely don't want to use it anymore.

On the first run a user-dirs.locale file is created containing the

locale that was used for the translation. This is used later by GUI

tools like `xdg-user-dirs-gtk-update` to detect if the locale was changed, letting you to migrate from the old names.

`xdg-user-dirs-update` is normally run automatically at the start of a user session to update the XDG user dirs according to the users locale.

## OPTIONS

The following options are understood:

`--help`

Print help output and exit.

`--force`

Update existing `user-dirs.dir`, but force a full reset. This means:

Don't reset nonexisting directories to HOME, rather recreate the directory. Never use backwards compatible non-translated names.

Always recreate `user-dirs.locale`.

`--dummy-output PATH`

Write the configuration to PATH instead of the default configuration file. Also, no directories are created.

`--set NAME PATH`

Sets the XDG user dir with the given name.

NAME should be one of the following:

DESKTOP

DOWNLOAD

TEMPLATES

PUBLICSHARE

DOCUMENTS

MUSIC

PICTURES

VIDEOS

PATH must be an absolute path, e.g. `$HOME/Some/Directory`.

## FILES

The XDG user dirs configuration is stored in the `user-dirs.dir` file in the location pointed to by the `XDG_CONFIG_HOME` environment variable.

## ENVIRONMENT

The `XDG_CONFIG_HOME` environment variable determines where the

user-dirs.dirs file is located.

#### SEE ALSO

xdg-user-dir(1), user-dirs.dirs(5), user-dirs.defaults(5), user-dirs.conf(5).

XDG

XDG-USER-DIRS-UPD(1)