



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'xencrypt.3'

\$ man xencrypt.3

XCRYPT(3) Linux Programmer's Manual XCRYPT(3)

NAME

xencrypt, xdecrypt, passwd2des - RFS password encryption

SYNOPSIS

```
#include <rpc/des_crypt.h>

void passwd2des(char *passwd, char *key);

int xencrypt(char *secret, char *passwd);

int xdecrypt(char *secret, char *passwd);
```

DESCRIPTION

WARNING: Do not use these functions in new code. They do not achieve any type of acceptable cryptographic security guarantees.

The function passwd2des() takes a character string passwd of arbitrary length and fills a character array key of length 8. The array key is suitable for use as DES key. It has odd parity set in bit 0 of each byte. Both other functions described here use this function to turn their argument passwd into a DES key.

The xencrypt() function takes the ASCII character string secret given in hex, which must have a length that is a multiple of 16, encrypts it

using the DES key derived from passwd by passwd2des(), and outputs the result again in secret as a hex string of the same length.

The xdecrypt() function performs the converse operation.

RETURN VALUE

The functions xencrypt() and xdecrypt() return 1 on success and 0 on error.

VERSIONS

These functions are available in glibc since version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

??

?Interface ? Attribute ? Value ?

??

?passwd2des(), xencrypt(), xdecrypt() ? Thread safety ? MT-Safe ?

??

BUGS

The prototypes are missing from the abovementioned include file.

SEE ALSO

cbc_crypt(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.