

## NAME

Authen::SASL::Perl::LOGIN – Login Authentication class

## SYNOPSIS

```
use Authen::SASL qw(Perl);

$ssasl = Authen::SASL->new(
    mechanism => 'LOGIN',
    callback => {
        user => $user,
        pass => $pass
    },
);
```

## DESCRIPTION

This method implements the client and server part of the LOGIN SASL algorithm, as described in IETF Draft draft-murchison-sasl-login-XX.txt.

### CALLBACK

The callbacks used are:

#### *Client*

`user`

The username to be used for authentication

`pass`

The user's password to be used for authentication

#### *Server*

`getsecret(username)`

returns the password associated with `username`

`checkpass(username, password)`

returns true and false depending on the validity of the credentials passed in arguments.

## SEE ALSO

Authen::SASL, Authen::SASL::Perl

## AUTHORS

Software written by Graham Barr <gbarr@pobox.com>, documentation written by Peter Marschall <peter@adpm.de>. Server support by Yann Kerherve <yannk@cpan.org>

Please report any bugs, or post any suggestions, to the perl-ldap mailing list <perl-ldap@perl.org>

## COPYRIGHT

Copyright (c) 2002–2004 Graham Barr. All rights reserved. This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

Documentation Copyright (c) 2004 Peter Marschall. All rights reserved. This documentation is distributed, and may be redistributed, under the same terms as Perl itself.

Server support Copyright (c) 2009 Yann Kerherve. All rights reserved. This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.