

NAME

Debian::DictionariesCommon.pm – dictionaries–common library

SYNOPSIS

```
use Debian::DictionariesCommon q(:all)
$dictionaries = parseinfo ('/var/lib/dictionaries-common/ispell/iwolof');
loaddb ('ispell')
updatedb ('wordlist')
```

DESCRIPTION

Common functions for use from the dictionaries-common system.

CALLING FUNCTIONS

dico_checkroot

Check for rootness and fail if not.

build_emacsen_support

Put info from dicts info files into emacsen–ispell–dicts.el

build_jed_support

Put info from dicts info files into jed–ispell–dicts.sl

build_squirrelmail_support

Build support file for squirrelmail with a list of available dictionaries and associated spellchecker calls, in php format.

\$libdir = getlibdir(\$class)

Return info dir for given class.

\$default = dico_getsysdefault(\$class)

Return system default value for given class.

\$libdir = getuserdefault

Return value for user default ispell dictionary.

dico_get_spellchecker_params(\$class, \%language)

Get right params for \$class (currently unused) and \$language

\%dictionaries = loaddb(\$class)

Read class .db file and return a reference to a hash with its contents.

\%result = parseinfo(\$file)

Parse given info file and return a reference to a hash with the relevant data.

setsysdefault(\$value)

Set value for system default ispell dictionary.

setuserdefault

Set value for user default ispell dictionary, after asking to select it from the available values.

updatedb(\$class)

Parse info files for given class and update class .db file under dictionaries-common cache dir.

SEE ALSO

Debian dictionaries-common policy.

AUTHORS

Rafael Laboissiere

Agustin Martin