

NAME

Font::TTF::Features::Size – Class for Character Variants Feature Parameters

DESCRIPTION

Handles the Feature Parameters values for Character Variants features

INSTANCE VARIABLES**INFILE**

The read file handle

OFFSET

Location of the file in the input file

Format

Table format – set to 0

UINameID

The 'name' table name ID that specifies a string (or strings, for multiple languages) for a user-interface label for this feature

TooltipNameID

The 'name' table name ID for tooltip text for the feature

SampleTextNameID

The 'name' table name ID for sample text to illustrate the feature

NumNamedParms

The number of named parameters

FirstNamedParmID

The 'name' table name ID for the first named parameter

Characters

An array holding the unicode values of the characters for which the feature provides glyph variants

METHODS**`$t->read`**

Reads the Feature Params

`$t->out($fh)`

Writes the FeatureParams table to the output

`Font::TTF::Features::Sset->new()`

Creates a new FeatureParams object. Values for INFILE and OFFSET can be passed as parameters

AUTHOR

David Raymond <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998–2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details, see the full text of the license in the file LICENSE.