

NAME

Font::TTF::Head – The head table for a TTF Font

DESCRIPTION

This is a very basic table with just instance variables as described in the TTF documentation, using the same names. One of the most commonly used is `unitsPerEm`.

INSTANCE VARIABLES

The head table has no internal instance variables beyond those common to all tables and those specified in the standard:

```

version
fontRevision
checksumAdjustment
magicNumber
flags
unitsPerEm
created
modified
xMin
yMin
xMax
yMax
macStyle
lowestRecPEM
fontDirectionHint
indexToLocFormat
glyphDataFormat

```

The two dates are held as an array of two unsigned longs (32–bits)

METHODS**`$t->read`**

Reads the table into memory thanks to some utility functions

`$t->out($fh)`

Writes the table to a file either from memory or by copying. If in memory (which is usually) the `checksumAdjustment` field is set to 0 as per the default if the file checksum is not to be considered.

`$t->minsize()`

Returns the minimum size this table can be. If it is smaller than this, then the table must be bad and should be deleted or whatever.

`$t->XML_element($context, $depth, $key, $value)`

Handles date process for the XML exporter

`$t->update`

Updates the head table based on the glyph data and the hmtx table

`$t->getdate($is_create)`

Converts font modification time (or creation time if `$is_create` is set) to a 32–bit integer as returned from `time()`. Returns undef if the value is out of range, either before the epoch or after the maximum storable time.

`$t->setdate($time, $is_create)`

Sets the time information for modification (or creation time if `$is_create` is set) according to the 32–bit time information.

BUGS

None known

AUTHOR

Martin Hosken <<http://scripts.sil.org/FontUtils>>.

LICENSING

Copyright (c) 1998–2016, SIL International (<http://www.sil.org>)

This module is released under the terms of the Artistic License 2.0. For details, see the full text of the license in the file LICENSE.