

NAME

HTML::FormatRTF – Format HTML as RTF

VERSION

version 2.12

SYNOPSIS

```
use HTML::FormatRTF;

my $out_file = "test.rtf";
open(RTF, ">$out_file")
  or die "Can't write-open $out_file: $!\nAborting";

print RTF HTML::FormatRTF->format_file(
    'test.html',
    'fontname_headings' => "Verdana",
);
close(RTF);
```

DESCRIPTION

HTML::FormatRTF is a class for objects that you use to convert HTML to RTF. There is currently no proper support for tables or forms.

This is a subclass of HTML::Formatter, whose documentation you should consult for more information on underlying methods such as `new`, `format`, `format_file` etc

You can specify any of the following parameters in the call to `new`, `format_file`, or `format_string`:

`lm` Amount of *extra* indenting to apply to the left margin, in twips (*twentieths of a point*). Default is 0.

So if you wanted the left margin to be an additional half inch larger, you'd set `lm => 720` (since there's 1440 twips in an inch). If you wanted it to be about 1.5cm larger, you'd set `lw => 850` (since there's about 567 twips in a centimeter).

`rm` Amount of *extra* indenting to apply to the right margin, in twips (*twentieths of a point*). Default is 0.

`normal_halfpoint_size`

This is the size of normal text in the document, in *half*-points. The default value is 22, meaning that normal text is in 11 point.

`header_halfpoint_size`

This is the size of text used in the document's page-header, in *half*-points. The default value is 17, meaning that normal text is in 7.5 point. Currently, the header consists just of "p. *pagenumber*" in the upper-right-hand corner, and cannot be disabled.

`head1_halfpoint_size ... head6_halfpoint_size`

These control the font size of each heading level, in half-twips. For example, the default for `head3_halfpoint_size` is 25, meaning that HTML `<h3>...</h3>` text will be in 12.5 point text (in addition to being underlined and in the heading font).

`codeblock_halfpoint_size`

This controls the font size (in half-points) of the text used for `<pre>...</pre>` text. By default, it is 18, meaning 9 point.

`fontname_body`

This option controls what font is to be used for the body of the text — that is, everything other than heading text and text in `pre/code/tt` elements. The default value is currently "Times". Other handy values I can suggest using are "Georgia" or "Bookman Old Style".

`fontname_code`

This option controls what font is to be used for text in `pre/code/tt` elements. The default value is currently "Courier New".

fontname_headings

This option controls what font name is to be used for headings. You can use the same font as `fontname_body`, but I prefer a sans-serif font, so the default value is currently “Arial”. Also consider “Tahoma” and “Verdana”.

document_language

This option controls what Microsoft language number will be specified as the language for this document. The current default value is 1033, for US English. Consult an RTF reference for other language numbers.

hr_width

This option controls how many underline characters will be used for rendering a “<hr>” tag. Its default value is currently 50. You can usually leave this alone, but under some circumstances you might want to use a smaller or larger number.

no_prolog

If this option is set to a true value, `HTML::FormatRTF` will make a point of *not* emitting the RTF prolog before the document. By default, this is off, meaning that `HTML::FormatRTF` *will* emit the prolog. This option is of interest only to advanced users.

no_trailer

If this option is set to a true value, `HTML::FormatRTF` will make a point of *not* emitting the RTF trailer at the end of the document. By default, this is off, meaning that `HTML::FormatRTF` *will* emit the bit of RTF that ends the document. This option is of interest only to advanced users.

SEE ALSO

`HTML::Formatter`, `RTF::Writer`

INSTALLATION

See `perlmodinstall` for information and options on installing Perl modules.

BUGS AND LIMITATIONS

You can make new bug reports, and view existing ones, through the web interface at <http://rt.cpan.org/Public/Dist/Display.html?Name=HTML-Format>.

AVAILABILITY

The project homepage is <https://metacpan.org/release/HTML-Format>.

The latest version of this module is available from the Comprehensive Perl Archive Network (CPAN). Visit <http://www.perl.com/CPAN/> to find a CPAN site near you, or see <https://metacpan.org/module/HTML::Format/>.

AUTHORS

- Nigel Metheringham <nigelm@cpan.org>
- Sean M Burke <sburke@cpan.org>
- Gisle Aas <gisle@ActiveState.com>

COPYRIGHT AND LICENSE

This software is copyright (c) 2015 by Nigel Metheringham, 2002–2005 Sean M Burke, 1999–2002 Gisle Aas.

This is free software; you can redistribute it and/or modify it under the same terms as the Perl 5 programming language system itself.