

NAME

Lintian::Processable::Orig – access to collected data about the upstream (orig) sources

SYNOPSIS

```
use Lintian::Processable;
my $processable = Lintian::Processable::Binary->new;
```

DESCRIPTION

Lintian::Processable::Orig provides an interface to collected data about the upstream (orig) sources.

INSTANCE METHODS

`orig`

Returns the index for `orig.tar.gz`.

`orig_index (FILE)`

Like “index” except `orig_index` is based on the “orig tarballs” of the source packages.

For native packages “index” and “orig_index” are generally identical.

NB: If `sorted_index` includes a debian packaging, it is was contained in upstream part of the source package (or the package is native).

Needs-Info requirements for using *orig_index*: `src-orig-index`

`sorted_orig_index`

`orig_index_resolved_path(PATH)`

Resolve `PATH` (relative to the root of the package) and return the entry denoting the resolved path.

The resolution is done using `resolve_path`.

NB: If `orig_index_resolved_path` includes a debian packaging, it is was contained in upstream part of the source package (or the package is native).

Needs-Info requirements for using *orig_index_resolved_path*: Same as `orig_index`

AUTHOR

Originally written by Felix Lechner <felix.lechner@lease-up.com> for Lintian.

SEE ALSO

lintian (1)