

NAME

XML::LibXML::Dtd – XML::LibXML DTD Handling

SYNOPSIS

```
use XML::LibXML;

$dtd = XML::LibXML::Dtd->new($public_id, $system_id);
$dtd = XML::LibXML::Dtd->parse_string($dtd_str);
$publicId = $dtd->getName();
$publicId = $dtd->publicId();
$systemId = $dtd->systemId();
```

DESCRIPTION

This class holds a DTD. You may parse a DTD from either a string, or from an external SYSTEM identifier.

No support is available as yet for parsing from a filehandle.

XML::LibXML::Dtd is a sub-class of XML::LibXML::Node, so all the methods available to nodes (particularly **toString()**) are available to Dtd objects.

METHODS**new**

```
$dtd = XML::LibXML::Dtd->new($public_id, $system_id);
```

Parse a DTD from the system identifier, and return a DTD object that you can pass to `$doc->is_valid()` or `$doc->validate()`.

```
my $dtd = XML::LibXML::Dtd->new(
    "SOME // Public / ID / 1.0",
    "test.dtd"
);
my $doc = XML::LibXML->new->parse_file("test.xml");
$doc->validate($dtd);
```

parse_string

```
$dtd = XML::LibXML::Dtd->parse_string($dtd_str);
```

The same as **new()** above, except you can parse a DTD from a string. Note that parsing from string may fail if the DTD contains external parametric-entity references with relative URLs.

getName

```
$publicId = $dtd->getName();
```

Returns the name of DTD; i.e., the name immediately following the DOCTYPE keyword.

publicId

```
$publicId = $dtd->publicId();
```

Returns the public identifier of the external subset.

systemId

```
$systemId = $dtd->systemId();
```

Returns the system identifier of the external subset.

AUTHORS

Matt Sergeant, Christian Glahn, Petr Pajas

VERSION

2.0134

COPYRIGHT

2001–2007, AxKit.com Ltd.

2002–2006, Christian Glahn.

2006–2009, Petr Pajas.

LICENSE

This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.