

NAME

XtErrorMsg, XtSetErrorMsgHandler, XtWarningMsg, XtSetWarningMsgHandler – high-level error handlers

SYNTAX

```
void XtErrorMsg(String name, String type, String class, String default, String *params, Cardinal
                *num_params);
void XtSetErrorMsgHandler(XtErrorMsgHandler msg_handler);
void XtSetWarningMsgHandler(XtErrorMsgHandler msg_handler);
void XtWarningMsg(String name, String type, String class, String default, String *params, Cardinal
                 *num_params);
```

ARGUMENTS

<i>class</i>	Specifies the resource class.
<i>default</i>	Specifies the default message to use.
<i>name</i>	Specifies the general kind of error.
<i>type</i>	Specifies the detailed name of the error.
<i>msg_handler</i>	Specifies the new fatal error procedure, which should not return or the nonfatal error procedure, which usually returns.
<i>num_params</i>	Specifies the number of values in the parameter list.
<i>params</i>	Specifies a pointer to a list of values to be stored in the message.

DESCRIPTION

The **XtErrorMsg** function has been superseded by **XtAppErrorMsg**.

The **XtSetErrorMsgHandler** function has been superseded by **XtAppSetErrorMsgHandler**.

The **XtSetWarningMsgHandler** function has been superseded by **XtAppSetWarningMsgHandler**.

The **XtWarningMsg** function has been superseded by **XtAppWarningMsg**.

SEE ALSO

XtAppErrorMsg(3)
X Toolkit Intrinsics – C Language Interface
Xlib – C Language X Interface