NAME

aptitude-create-state-bundle - bundle the current aptitude state

SYNOPSIS

aptitude-create-state-bundle [<options>...] <output-file>

DESCRIPTION

Note

This command is mostly for internal use and bug reporting in exceptional cases, it is not intended for end-users under normal circumstances.

aptitude–create–state–bundle produces a compressed archive storing the files that are required to replicate the current package archive state. The following files and directories are included in the bundle:

Command-line reference

- \$HOME/.aptitude
- /var/lib/aptitude
- /var/lib/apt
- /var/cache/apt/*.bin
- /etc/apt
- /var/lib/dpkg/status

The output of this program can be used as an argument to **aptitude-run-state-bundle**(1).

OPTIONS

--force-bzip2

Override the autodetection of which compression algorithm to use. By default, **aptitude–create–state–bundle** uses **bzip2**(1) if it is available, and **gzip**(1) otherwise. Passing this option forces the use of **bzip2** even if it doesn't appear to be available.

--force-gzip

Override the autodetection of which compression algorithm to use. By default, **aptitude–create–state–bundle** uses **bzip2**(1) if it is available, and **gzip**(1) otherwise. Passing this option forces the use of **gzip** even if **bzip2** is available.

--help

Print a brief usage message, then exit.

--print-inputs

Instead of creating a bundle, display a list of the files and directories that the program would include if it generated a bundle.

FILE FORMAT

The bundle file is simply a **tar**(1) file compressed with **bzip2**(1) or **gzip**(1), with each of the input directory trees rooted at ".".

SEE ALSO

aptitude-run-state-bundle(1), aptitude(8), apt(8)

AUTHORS

Daniel Burrows dburrows@debian.org

Main author of the document.

Manuel A. Fernandez Montecelo <mafm@debian.org>

Main maintainer after Daniel Burrows, documentation about new features, corrections and formatting.

COPYRIGHT

Copyright 2007 Daniel Burrows.

This manual page is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This manual page is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110–1301 USA.