

**NAME**

**bundle-add** – Add gem to the Gemfile and run bundle install

**SYNOPSIS**

**bundle add** *GEM\_NAME* [**--group**=*GROUP*] [**--version**=*VERSION*] [**--source**=*SOURCE*] [**--git**=*GIT*] [**--branch**=*BRANCH*] [**--skip-install**] [**--strict**] [**--optimistic**]

**DESCRIPTION**

Adds the named gem to the Gemfile and run **bundle install**. **bundle install** can be avoided by using the flag **--skip-install**.

Example:

```
bundle add rails
bundle add rails --version "< 3.0, > 1.1"
bundle add rails --version "~> 5.0.0" --source "https://gems.example.com" --group "development"
bundle add rails --skip-install
bundle add rails --group "development, test"
```

**OPTIONS****--version, -v**

Specify version requirements(s) for the added gem.

**--group, -g**

Specify the group(s) for the added gem. Multiple groups should be separated by commas.

**--source, , -s**

Specify the source for the added gem.

**--git**

Specify the git source for the added gem.

**--branch**

Specify the git branch for the added gem.

**--skip-install**

Adds the gem to the Gemfile but does not install it.

**--optimistic**

Adds optimistic declaration of version

**--strict**

Adds strict declaration of version