

**NAME**

**bundle-binstubs** – Install the binstubs of the listed gems

**SYNOPSIS**

**bundle binstubs** *GEM\_NAME* [--force] [--path PATH] [--standalone]

**DESCRIPTION**

Binstubs are scripts that wrap around executables. Bundler creates a small Ruby file (a binstub) that loads Bundler, runs the command, and puts it into **bin/**. Binstubs are a shortcut—or alternative—to always using **bundle exec**. This gives you a file that can be run directly, and one that will always run the correct gem version used by the application.

For example, if you run **bundle binstubs rspec-core**, Bundler will create the file **bin/rspec**. That file will contain enough code to load Bundler, tell it to load the bundled gems, and then run rspec.

This command generates binstubs for executables in **GEM\_NAME**. Binstubs are put into **bin**, or the **--path** directory if one has been set. Calling binstubs with [GEM [GEM]] will create binstubs for all given gems.

**OPTIONS****--force**

Overwrite existing binstubs if they exist.

**--path** The location to install the specified binstubs to. This defaults to **bin**.

**--standalone**

Makes binstubs that can work without depending on Rubygems or Bundler at runtime.

**--shebang**

Specify a different shebang executable name than the default (default 'ruby')

**BUNDLE INSTALL --BINSTUBS**

To create binstubs for all the gems in the bundle you can use the **--binstubs** flag in `bundle install(1)` *bundle-install.1.html*.