

NAME

openssl-crl, crl – CRL utility

SYNOPSIS

openssl crl [**-help**] [**-inform PEM|DER**] [**-outform PEM|DER**] [**-text**] [**-in filename**] [**-out filename**] [**-nameopt option**] [**-noout**] [**-hash**] [**-issuer**] [**-lastupdate**] [**-nextupdate**] [**-CAfile file**] [**-CApath dir**]

DESCRIPTION

The **crl** command processes CRL files in DER or PEM format.

OPTIONS**-help**

Print out a usage message.

-inform DER|PEM

This specifies the input format. **DER** format is DER encoded CRL structure. **PEM** (the default) is a base64 encoded version of the DER form with header and footer lines.

-outform DER|PEM

This specifies the output format, the options have the same meaning and default as the **-inform** option.

-in filename

This specifies the input filename to read from or standard input if this option is not specified.

-out filename

Specifies the output filename to write to or standard output by default.

-text

Print out the CRL in text form.

-nameopt option

Option which determines how the subject or issuer names are displayed. See the description of **-nameopt** in **x509(1)**.

-noout

Don't output the encoded version of the CRL.

-hash

Output a hash of the issuer name. This can be use to lookup CRLs in a directory by issuer name.

-hash_old

Outputs the "hash" of the CRL issuer name using the older algorithm as used by OpenSSL before version 1.0.0.

-issuer

Output the issuer name.

-lastupdate

Output the lastUpdate field.

-nextupdate

Output the nextUpdate field.

-CAfile file

Verify the signature on a CRL by looking up the issuing certificate in **file**.

-CApath dir

Verify the signature on a CRL by looking up the issuing certificate in **dir**. This directory must be a standard certificate directory: that is a hash of each subject name (using **x509 -hash**) should be linked to each certificate.

NOTES

The PEM CRL format uses the header and footer lines:

```
-----BEGIN X509 CRL-----  
-----END X509 CRL-----
```

EXAMPLES

Convert a CRL file from PEM to DER:

```
openssl crl -in crl.pem -outform DER -out crl.der
```

Output the text form of a DER encoded certificate:

```
openssl crl -in crl.der -inform DER -text -noout
```

BUGS

Ideally it should be possible to create a CRL using appropriate options and files too.

SEE ALSO

cr2pkcs7(1), **ca**(1), **x509**(1)

COPYRIGHT

Copyright 2000–2018 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the OpenSSL license (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.