

NAME

expm1, expm1f, expm1l – exponential minus 1

SYNOPSIS

```
#include <math.h>
```

```
double expm1(double x);
```

```
float expm1f(float x);
```

```
long double expm1l(long double x);
```

Link with `-lm`.

Feature Test Macro Requirements for glibc (see [feature_test_macros\(7\)](#)):

```
expm1():
```

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

```
|| _XOPEN_SOURCE >= 500
```

```
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

```
expm1f(), expm1l():
```

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

```
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

DESCRIPTION

These functions return a value equivalent to

$$\exp(x) - 1$$

The result is computed in a way that is accurate even if the value of x is near zero—a case where $\exp(x) - 1$ would be inaccurate due to subtraction of two numbers that are nearly equal.

RETURN VALUE

On success, these functions return $\exp(x) - 1$.

If x is a NaN, a NaN is returned.

If x is +0 (−0), +0 (−0) is returned.

If x is positive infinity, positive infinity is returned.

If x is negative infinity, −1 is returned.

If the result overflows, a range error occurs, and the functions return `-HUGE_VAL`, `-HUGE_VALF`, or `-HUGE_VALL`, respectively.

ERRORS

See [math_error\(7\)](#) for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Range error, overflow

`errno` is set to `ERANGE` (but see [BUGS](#)). An overflow floating-point exception (`FE_OVERFLOW`) is raised.

ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

Interface	Attribute	Value
<code>expm1()</code> , <code>expm1f()</code> , <code>expm1l()</code>	Thread safety	MT-Safe

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

BUGS

For some large negative x values (where the function result approaches -1), **expm1()** raises a bogus underflow floating-point exception.

For some large positive x values, **expm1()** raises a bogus invalid floating-point exception in addition to the expected overflow exception, and returns a NaN instead of positive infinity.

Before version 2.11, the glibc implementation did not set *errno* to **ERANGE** when a range error occurred.

SEE ALSO

exp(3), **log(3)**, **log1p(3)**

COLOPHON

This page is part of release 5.05 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.