

NAME

`fgetws` – read a wide-character string from a FILE stream

SYNOPSIS

```
#include <wchar.h>
```

```
wchar_t *fgetws(wchar_t *ws, int n, FILE *stream);
```

DESCRIPTION

The `fgetws()` function is the wide-character equivalent of the `fgets(3)` function. It reads a string of at most $n-1$ wide characters into the wide-character array pointed to by `ws`, and adds a terminating null wide character (L'\0'). It stops reading wide characters after it has encountered and stored a newline wide character. It also stops when end of stream is reached.

The programmer must ensure that there is room for at least n wide characters at `ws`.

For a nonlocking counterpart, see `unlocked_stdio(3)`.

RETURN VALUE

The `fgetws()` function, if successful, returns `ws`. If end of stream was already reached or if an error occurred, it returns NULL.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

Interface	Attribute	Value
<code>fgetws()</code>	Thread safety	MT-Safe

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

NOTES

The behavior of `fgetws()` depends on the `LC_CTYPE` category of the current locale.

In the absence of additional information passed to the `fopen(3)` call, it is reasonable to expect that `fgetws()` will actually read a multibyte string from the stream and then convert it to a wide-character string.

This function is unreliable, because it does not permit to deal properly with null wide characters that may be present in the input.

SEE ALSO

`fgetwc(3)`, `unlocked_stdio(3)`

COLOPHON

This page is part of release 5.05 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.