NAME

lrint, lrintf, lrintl, llrint, llrintf, llrintl − round to nearest integer

SYNOPSIS

#include <math.h>

long int lrint(double *x***);**
long int lrintf(float *x***);**
long int lrintl(long double *x***);**

long long int llrint(double *x***);**
long long int llrintf(float *x***);**
long long int llrintl(long double *x***);**

Link with *−lm*.

Feature Test Macro Requirements for glibc (see **feature_test_macros**(7)):

All functions shown above:
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L

DESCRIPTION

These functions round their argument to the nearest integer value, using the current rounding direction (see **fesetround**(3)).

Note that unlike the **rint**(3) family of functions, the return type of these functions differs from that of their arguments.

RETURN VALUE

These functions return the rounded integer value.

If *x* is a NaN or an infinity, or the rounded value is too large to be stored in a *long* (*long long* in the case of the **ll*** functions), then a domain error occurs, and the return value is unspecified.

ERRORS

See **math_error**(7) for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Domain error: *x* is a NaN or infinite, or the rounded value is too large
An invalid floating-point exception (**FE_INVALID**) is raised.

These functions do not set *errno*.

VERSIONS

These functions first appeared in glibc in version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes**(7).

Interface	Attribute	Value
lrint(), **lrintf**(), **lrintl**(), **llrint**(), **llrintf**(), **llrintl**()	Thread safety	MT-Safe

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

SEE ALSO

ceil(3), **floor**(3), **lround**(3), **nearbyint**(3), **rint**(3), **round**(3)

COLOPHON

This page is part of release 5.05 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man−pages/.