

NAME

`mq_receive`, `mq_timedreceive` – receive a message from a message queue

SYNOPSIS

```
#include <mqqueue.h>

ssize_t mq_receive(mqd_t mqdes, char *msg_ptr,
                  size_t msg_len, unsigned int *msg_prio);

#include <time.h>
#include <mqqueue.h>

ssize_t mq_timedreceive(mqd_t mqdes, char *msg_ptr,
                       size_t msg_len, unsigned int *msg_prio,
                       const struct timespec *abs_timeout);
```

Link with `-lrt`.

Feature Test Macro Requirements for glibc (see `feature_test_macros(7)`):

```
mq_timedreceive():
    _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

`mq_receive()` removes the oldest message with the highest priority from the message queue referred to by the message queue descriptor `mqdes`, and places it in the buffer pointed to by `msg_ptr`. The `msg_len` argument specifies the size of the buffer pointed to by `msg_ptr`; this must be greater than or equal to the `mq_msgsize` attribute of the queue (see `mq_getattr(3)`). If `msg_prio` is not NULL, then the buffer to which it points is used to return the priority associated with the received message.

If the queue is empty, then, by default, `mq_receive()` blocks until a message becomes available, or the call is interrupted by a signal handler. If the `O_NONBLOCK` flag is enabled for the message queue description, then the call instead fails immediately with the error **EAGAIN**.

`mq_timedreceive()` behaves just like `mq_receive()`, except that if the queue is empty and the `O_NONBLOCK` flag is not enabled for the message queue description, then `abs_timeout` points to a structure which specifies how long the call will block. This value is an absolute timeout in seconds and nanoseconds since the Epoch, 1970-01-01 00:00:00 +0000 (UTC), specified in the following structure:

```
struct timespec {
    time_t tv_sec;           /* seconds */
    long   tv_nsec;        /* nanoseconds */
};
```

If no message is available, and the timeout has already expired by the time of the call, `mq_timedreceive()` returns immediately.

RETURN VALUE

On success, `mq_receive()` and `mq_timedreceive()` return the number of bytes in the received message; on error, `-1` is returned, with `errno` set to indicate the error.

ERRORS**EAGAIN**

The queue was empty, and the `O_NONBLOCK` flag was set for the message queue description referred to by `mqdes`.

EBADF

The descriptor specified in `mqdes` was invalid or not opened for reading.

EINTR

The call was interrupted by a signal handler; see `signal(7)`.

EINVAL

The call would have blocked, and `abs_timeout` was invalid, either because `tv_sec` was less than zero, or because `tv_nsec` was less than zero or greater than 1000 million.

EMSGSIZE

msg_len was less than the *mq_msgsize* attribute of the message queue.

ETIMEDOUT

The call timed out before a message could be transferred.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
mq_receive() , mq_timedreceive()	Thread safety	MT-Safe

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

NOTES

On Linux, **mq_timedreceive()** is a system call, and **mq_receive()** is a library function layered on top of that system call.

SEE ALSO

mq_close(3), **mq_getattr(3)**, **mq_notify(3)**, **mq_open(3)**, **mq_send(3)**, **mq_unlink(3)**, **mq_overview(7)**, **time(7)**

COLOPHON

This page is part of release 5.05 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.