

NAME

msgattrib – attribute matching and manipulation on message catalog

SYNOPSIS

msgattrib [*OPTION*] [*INPUTFILE*]

DESCRIPTION

Filters the messages of a translation catalog according to their attributes, and manipulates the attributes.

Mandatory arguments to long options are mandatory for short options too.

Input file location:

INPUTFILE

input PO file

-D, --directory=DIRECTORY

add DIRECTORY to list for input files search

If no input file is given or if it is -, standard input is read.

Output file location:

-o, --output-file=FILE

write output to specified file

The results are written to standard output if no output file is specified or if it is -.

Message selection:

--translated

keep translated, remove untranslated messages

--untranslated

keep untranslated, remove translated messages

--no-fuzzy

remove 'fuzzy' marked messages

--only-fuzzy

keep 'fuzzy' marked messages

--no-obsolete

remove obsolete #~ messages

--only-obsolete

keep obsolete #~ messages

Attribute manipulation:

--set-fuzzy

set all messages 'fuzzy'

--clear-fuzzy

set all messages non-'fuzzy'

--set-obsolete

set all messages obsolete

--clear-obsolete

set all messages non-obsolete

--previous

when setting 'fuzzy', keep previous msgids of translated messages.

--clear-previous

remove the "previous msgid" from all messages

--empty

when removing 'fuzzy', also set msgstr empty

--only-file=FILE.po
 manipulate only entries listed in FILE.po
--ignore-file=FILE.po
 manipulate only entries not listed in FILE.po
--fuzzy
 synonym for **--only-fuzzy --clear-fuzzy**
--obsolete
 synonym for **--onlyObsolete --clearObsolete**

Input file syntax:

-P, --properties-input
 input file is in Java .properties syntax
--stringtable-input
 input file is in NeXTstep/GNUstep .strings syntax

Output details:

--color
 use colors and other text attributes always
--color=WHEN
 use colors and other text attributes if WHEN. WHEN may be 'always', 'never', 'auto', or 'html'.
--style=STYLEFILE
 specify CSS style rule file for **--color**
-e, --no-escape
 do not use C escapes in output (default)
-E, --escape
 use C escapes in output, no extended chars
--force-po
 write PO file even if empty
-i, --indent
 write the .po file using indented style
--no-location
 do not write '#: filename:line' lines
-n, --add-location
 generate '#: filename:line' lines (default)
--strict
 write out strict Uniforum conforming .po file
-p, --properties-output
 write out a Java .properties file
--stringtable-output
 write out a NeXTstep/GNUstep .strings file
-w, --width=NUMBER
 set output page width
--no-wrap
 do not break long message lines, longer than the output page width, into several lines
-s, --sort-output
 generate sorted output

-F, --sort-by-file
sort output by file location

Informative output:

-h, --help
display this help and exit
-V, --version
output version information and exit

AUTHOR

Written by Bruno Haible.

REPORTING BUGS

Report bugs to <bug-gnu-gettext@gnu.org>.

COPYRIGHT

Copyright © 2001-2016 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later
<<http://gnu.org/licenses/gpl.html>>

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

The full documentation for **msgattrib** is maintained as a Texinfo manual. If the **info** and **msgattrib** programs are properly installed at your site, the command

info msgattrib

should give you access to the complete manual.