

NAME

msgunfmt – uncompile message catalog from binary format

SYNOPSIS

msgunfmt [*OPTION*] [*FILE*]...

DESCRIPTION

Convert binary message catalog to Uniform style .po file.

Mandatory arguments to long options are mandatory for short options too.

Operation mode:

-j, --java

Java mode: input is a Java ResourceBundle class

--csharp

C# mode: input is a .NET .dll file

--csharp-resources

C# resources mode: input is a .NET .resources file

--tcl Tcl mode: input is a tcl/msgcat .msg file

Input file location:

FILE ...

input .mo files

If no input file is given or if it is -, standard input is read.

Input file location in Java mode:

-r, --resource=RESOURCE

resource name

-l, --locale=LOCALE

locale name, either language or language_COUNTRY

The class name is determined by appending the locale name to the resource name, separated with an underscore. The class is located using the CLASSPATH.

Input file location in C# mode:

-r, --resource=RESOURCE

resource name

-l, --locale=LOCALE

locale name, either language or language_COUNTRY

-d DIRECTORY

base directory for locale dependent .dll files

The **-l** and **-d** options are mandatory. The .dll file is located in a subdirectory of the specified directory whose name depends on the locale.

Input file location in Tcl mode:

-l, --locale=LOCALE

locale name, either language or language_COUNTRY

-d DIRECTORY

base directory of .msg message catalogs

The **-l** and **-d** options are mandatory. The .msg file is located in the specified directory.

Output file location:

-o, --output-file=FILE

write output to specified file

The results are written to standard output if no output file is specified or if it is -.

Output details:

- color**
use colors and other text attributes always
- color=WHEN**
use colors and other text attributes if WHEN. WHEN may be 'always', 'never', 'auto', or 'html'.
- style=STYLEFILE**
specify CSS style rule file for **--color**
- e, --no-escape**
do not use C escapes in output (default)
- E, --escape**
use C escapes in output, no extended chars
- force-po**
write PO file even if empty
- i, --indent**
write indented output style
- strict**
write strict uniform style
- p, --properties-output**
write out a Java .properties file
- stringtable-output**
write out a NeXTstep/GNUstep .strings file
- w, --width=NUMBER**
set output page width
- no-wrap**
do not break long message lines, longer than the output page width, into several lines
- s, --sort-output**
generate sorted output

Informative output:

- h, --help**
display this help and exit
- V, --version**
output version information and exit
- v, --verbose**
increase verbosity level

AUTHOR

Written by Ulrich Drepper.

REPORTING BUGS

Report bugs to <bug-gnu-gettext@gnu.org>.

COPYRIGHT

Copyright © 1995-1998, 2000-2016 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

The full documentation for **msgunfmt** is maintained as a Texinfo manual. If the **info** and **msgunfmt** programs are properly installed at your site, the command

info msgunfmt

should give you access to the complete manual.