NAME

MUTTER - Clutter based compositing GTK2 Window Manager

SYNOPSIS

```
mutter [--display=DISPLAY] [--replace] [--sm-client-id=ID] [--sm-disable] [--sm-save-file=FILE-NAME] [--version] [--help]
```

DESCRIPTION

This manual page documents briefly **mutter**.

mutter is a minimal X window manager aimed at nontechnical users and is designed to integrate well with the GNOME desktop. **mutter** lacks some features that may be expected by traditional UNIX or other technical users; these users may want to investigate other available window managers for use with GNOME or standalone.

OPTIONS

--display=DISPLAY

Connect to X display DISPLAY.

--replace

a window manager which is running is replaced by **mutter**. Users are encouraged to change the GNOME window manager by running the new WM with the --replace or -replace option, and subsequently saving the session.

--sm-client-id=ID

Specify a session management *ID*.

--sm-disable

Disable the session management.

--sm-save-file=FILENAME

Load a session from FILENAME.

--version

Print the version number.

-?, --help

Show summary of options.

CONFIGURATION

mutter configuration can be found under *Preferences->Windows* and *Preferences->Keyboard Shortcuts* on the menu-panel. Advanced configuration can be achieved directly through gsettings.

SEE ALSO

mutter-message(1)

AUTHOR

The original manual page was written by Thom May <thom@debian.org>. It was updated by Akira TAGOH <tagoh@debian.org> for the Debian GNU/Linux system (with permission to use by others), and then updated by Luke Morton and Philip O'Brien for inclusion in mutter.