

NAME

paperconfig – configure the system default paper size

SYNOPSIS

paperconfig [**-v,--version**] [**-h,--help**] [**-p, --paper** *papername* | **--force**]

DESCRIPTION

paperconfig sets the system (or default) paper to be used by tools using the **papersize** file. It can either ask interactively for the paper to use or be called non-interactively by scripts.

When the paper size has been changed, **paperconfig** notifies other packages of the change by running the scripts in the */etc/libpaper.d* directory.

OPTIONS

-v,--version

Print the version of **paperconfig** and exit.

-h,--help

Print help about usage and exit.

-p, --paper *papername*

Use *papername* if possible. If *papername* is not a valid paper, print an error message and exit.

--force

Force interactive selection of the system paper even if the actual paper is a valid one.

ENVIRONMENT

PAPERCONF Full path to a file containing the paper size to use; this file will be rewritten with the system paper size.

FILES

/etc/papersize

Contains the name of the system-wide default paper size to be used if the **PAPER-SIZE** variable is not set.

/etc/libpaper.d

Directory of scripts to run after the paper size has been changed. This package puts no scripts here, but other packages may. **run-parts** is used to run the scripts, therefore their names must comply with **run-part**'s naming requirements.

AUTHOR

Yves Arrouye <arrouye@debian.org>

SEE ALSO

paperconf(1)

papersize(5)