

NAME

rdma-link – rdma link configuration

SYNOPSIS

devlink [*OPTIONS*] **link** { *COMMAND* | **help** }

OPTIONS := { **-V**[*ersion*] | **-d**[*etails*] }

rdma link show [*DEV/PORT_INDEX*]

rdma link add **NAME** **type** **TYPE** **netdev** **NETDEV**

rdma link delete **NAME**

rdma link help

DESCRIPTION

rdma link show - display rdma link attributes

DEV/PORT_INDEX - specifies the RDMA link to show. If this argument is omitted all links are listed.

rdma link add NAME type TYPE netdev NETDEV - add an rdma link for the specified type to the network device

NAME - specifies the new name of the rdma link to add

TYPE - specifies which rdma type to use. Link types:

rxe - Soft RoCE driver

siw - Soft iWARP driver

NETDEV - specifies the network device to which the link is bound

rdma link delete NAME - delete an rdma link

NAME - specifies the name of the rdma link to delete

EXAMPLES

rdma link show

Shows the state of all rdma links on the system.

rdma link show mlx5_2/1

Shows the state of specified rdma link.

rdma link add rx_e_eth0 type rx_e netdev eth0

Adds a RXE link named rx_e_eth0 to network device eth0

rdma link del rx_e_eth0

Removes RXE link rx_e_eth0

SEE ALSO

rdma(8), **rdma-dev**(8), **rdma-resource**(8), **rdma-statistic**(8),

AUTHOR

Leon Romanovsky <leonro@mellanox.com>