

NAME rpm – lesser need options for rpm(8)**OPTIONS**

--predefine='*MACRO EXPR*'
Defines *MACRO* with value *EXPR*. before loading macro files.

Switching off features

--color [**never**|**auto**|**always**]
Use terminal colors for highlighting error and debug message. Default is turning colors on for ttys only (**auto**).

--nocontexts
Disable the SELinux plugin if available. This stops the plugin from setting SELinux contexts for files and scriptlets.

--noglob
Do not glob arguments when installing package files.

--nocaps
Don't verify capabilities of files.

--excludeconfigs, --noconfigs
Do not install configuration files.

--nohdrchk
Don't verify database header(s) when retrieved.

Debugging

-d, --debug
Print debugging information.

--deploops
Print dependency loops as warning.

--fsmdebug
Print debugging information of payload handling code.

--rpmfcdebug
Print debug information about files packaged.

--rpmiodebug
Print debug information about file IO.

--stats Print runtime statistics of often used functions.

Obsolete Options

-K, --checksig
See and use rpmkeys(8).

--nodoc
Do not install documentation. Use **--excludedocs** instead.

--promoteepoch
Enable obsolete epoch handling used in rpm 3.x time frame.

--prtpkts
OBSOLETE! Used to print the packages containing and representing the pgp keys for debugging purposes.