

NAME

snap-discard-ns – internal tool for discarding preserved namespaces of snappy applications

SYNOPSIS

snap-discard-ns [--from-snap-confine] SNAP_INSTANCE_NAME

DESCRIPTION

The *snap-discard-ns* is a program used internally by *snapd* to discard a preserved mount namespace of a particular snap.

OPTIONS

The `--from-snap-confine` option is used internally by `snap-confine` to tell `snap-discard-ns` that it is invoked from `snap-confine` and can disable locking.

ENVIRONMENT

snap-discard-ns responds to the following environment variables

SNAP_CONFINE_DEBUG:

When defined the program will print additional diagnostic information about the actions being performed. All the output goes to `stderr`.

FILES

snap-discard-ns uses the following files:

/run/snapd/ns/\$SNAP_INSTANCE_NAME.mnt: */run/snapd/ns/\$SNAP_INSTANCE_NAME.*.mnt*:

The preserved mount namespace that is unmounted and removed by *snap-discard-ns*. The second form is for the per-user mount namespace.

/run/snapd/ns/snap.\$SNAP_INSTANCE_NAME.fstab:

/run/snapd/ns/snap.\$SNAP_INSTANCE_NAME..user-fstab*:

The current mount profile of a preserved mount namespace that is removed by *snap-discard-ns*.

BUGS

Please report all bugs with <https://bugs.launchpad.net/snapd/+filebug>

AUTHOR

zygmunt.krynicki@canonical.com

COPYRIGHT

Canonical Ltd.