NAME

tan, tanf, tanl - tangent function

SYNOPSIS

```
#include <math.h>
double tan(double x);
float tanf(float x);
long double tanl(long double x);
```

Link with -lm.

Feature Test Macro Requirements for glibc (see **feature_test_macros**(7)):

```
tanf(), tanl():
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

| /* Glibc versions <= 2.19: */ BSD_SOURCE | _SVID_SOURCE

DESCRIPTION

These functions return the tangent of x, where x is given in radians.

RETURN VALUE

On success, these functions return the tangent of x.

If x is a NaN, a NaN is returned.

If x is positive infinity or negative infinity, a domain error occurs, and a NaN is returned.

If the correct result would overflow, a range error occurs, and the functions return HUGE_VAL, HUGE_VALF, or HUGE_VALL, respectively, with the mathematically correct sign.

ERRORS

See **math_error**(7) for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Domain error: x is an infinity

errno is set to EDOM (but see BUGS). An invalid floating-point exception (FE_INVALID) is raised.

Range error: result overflow

An overflow floating-point exception (**FE_OVERFLOW**) is raised.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes**(7).

Interface	Attribute	Value
tan(), tanf(), tanl()	Thread safety	MT-Safe

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

The variant returning double also conforms to SVr4, 4.3BSD, C89.

BUGS

Before version 2.10, the glibc implementation did not set errno to EDOM when a domain error occurred.

SEE ALSO

```
acos(3), asin(3), atan(3), atan(3), cos(3), ctan(3), sin(3)
```

COLOPHON

This page is part of release 5.05 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

2017-09-15