NAME
>   tasksel − a user interface for installing tasks

SYNOPSIS
>   tasksel install <task>
>
>   tasksel remove <task>
>
>   tasksel [options]

DESCRIPTION
>   tasksel shows all available tasks and allows to user to select ones to install

OPTIONS
>   **−t**, **−−test**
>   test mode; don't actually install or remove packages
>
>   **−−new−install**
>   automatically select some tasks without even displaying them to the user; default other tasks to on;
>   used during new Debian installs.
>
>   **−−list−tasks**
>   list on stdout the tasks that would be displayed in the tasksel interface
>
>   **−−task−packages** task
>   lists on stdout the packages that are available and part of the given task
>
>   Note that this option may be given more than once.
>
>   **−−task−desc** task
>   outputs the extended description of the given task
>
>   **−−debconf−apt−from** waypoint
>   Start the debconf-apt-progress bar here.
>
>   **−−debconf−apt−to** waypoint
>   End the debconf-apt-progress bar here.
>
>   **−−debconf−apt−progress** options
>   Pass the specified options to the debconf-apt-progress command that tasksel runs. These will be
>   appended to any **−−from** and **−−to** options constructed by tasksel itself based on
>   **−−debconf−apt−from** and **−−debconf−apt−to** options.

SEE ALSO
>   **dpkg** (8), **apt−get** (8)

FILES
>   */usr/share/tasksel/*.desc* and */usr/local/share/tasksel/*.desc* are used to define tasks.

AUTHOR
>   tasksel was written by Randolph Chung <tausq@debian.org> and Joey Hess <joeyh@debian.org>

HISTORY
>   This document first appeared with tasksel−1.0