

**NAME**

tipc-media – list or modify media properties

**SYNOPSIS**

**tipc media set** { **priority** *PRIORITY* | **tolerance** *TOLERANCE* | **window** *WINDOW* } **media** *MEDIA*

**tipc media get** { **priority** | **tolerance** | **window** } **media** *MEDIA*

**tipc media list**

**OPTIONS**

Options (flags) that can be passed anywhere in the command chain.

**-h, --help**

Show help about last valid command. For example **tipc media --help** will show media help and **tipc --help** will show general help. The position of the option in the string is irrelevant.

**DESCRIPTION****Media properties****priority**

Default link priority inherited by all bearers subsequently enabled on a media. For more info about link priority see **tipc-link(8)**

**tolerance**

Default link tolerance inherited by all bearers subsequently enabled on a media. For more info about link tolerance see **tipc-link(8)**

**window**

Default link window inherited by all bearers subsequently enabled on a media. For more info about link window see **tipc-link(8)**

**EXIT STATUS**

Exit status is 0 if command was successful or a positive integer upon failure.

**SEE ALSO**

**tipc(8)**, **tipc-bearer(8)**, **tipc-link(8)**, **tipc-nametable(8)**, **tipc-node(8)**, **tipc-peer(8)**, **tipc-socket(8)**

**REPORTING BUGS**

Report any bugs to the Network Developers mailing list <[netdev@vger.kernel.org](mailto:netdev@vger.kernel.org)> where the development and maintenance is primarily done. You do not have to be subscribed to the list to send a message there.

**AUTHOR**

Richard Alpe <[richard.alpe@ericsson.com](mailto:richard.alpe@ericsson.com)>